

ELECTRONIC BOOK HAVING ELECTRONIC COMMERCE FEATURES

Related Applications

This application is a continuation-in-part of U.S. Application Serial No. 07/991,074 entitled TELEVISION PROGRAM PACKAGING AND DELIVERY SYSTEM WITH MENU DRIVEN SUBSCRIBER ACCESS, filed December 9, 1992, and U.S. Application Serial No. 08/336,247 entitled ELECTRONIC BOOK SELECTION AND DELIVERY SYSTEM, filed November 7, 1994, and U.S. Application Serial No. 08/160,194 and PCT/ US93/11606 entitled ADVANCED SET-TOP TERMINAL FOR CABLE TELEVISION DELIVERY SYSTEMS, filed December 2, 1993, and U.S. Application Serial No. 08/906,469 entitled REPROGRAMMABLE TERMINAL FOR SUGGESTING PROGRAMS OFFERED ON A TELEVISION PROGRAM DELIVERY SYSTEM, filed August 5, 1997, and U.S. Application Serial No. 09/191,520 entitled DIGITAL BROADCAST PROGRAM ORDERING, filed November 13, 1998. These applications are incorporated by reference herein.

Also incorporated herein by reference are co-pending U.S. Application Serial No. 09/237,827, entitled ELECTRONIC BOOK HAVING LIBRARY CATALOG MENU AND SEARCHING FEATURES, filed January 27, 1999; U.S. Application Serial No. 09/237,828, entitled ELECTRONIC BOOK ELECTRONIC LINKS, filed January 27, 1999; U.S. Application Serial No. 09/289,956, entitled ELECTRONIC BOOK ALTERNATIVE DELIVERY METHODS, filed April 13, 1999; U.S. Application Serial No. 09/054,419, entitled TARGETED ADVERTISEMENT USING TELEVISION DELIVERY SYSTEMS, filed April 3, 1998; and U.S. Application Serial No. 09/400,296, entitled ELECTRONIC BOOK SECURITY AND COPYRIGHT PROTECTION SYSTEM, filed September 21, 1999.

Background Art

Sparked by the concept of an information superhighway, a revolution will take place in the distribution of books. Not since the introduction of Gutenberg's movable typeset printing has the world stood on the brink of such a revolution in the distribution of text material. The definition of the word "book" will change drastically in the near

1 future. Due to reasons such as security, convenience, cost, and other technical problems,
2 book and magazine publishers are currently only able to distribute their products in paper
3 form. This invention solves the problems encountered by publishers.

4 Technical Field And Brief Summary Of Invention

5 The electronic book selection and delivery system is a new way to distribute
6 books to bookstores, public libraries, schools and consumers. The technological
7 breakthroughs of this invention provide a secure electronic system for both delivering
8 selected books and receiving payments. The system has an unusual combination of
9 features that provides the consumer with a daily use household appliance that has a high
10 tech aura while being very practical, portable, and easy to use.

11 An advantage of the system is that it eliminates the distribution of any physical
12 object such as a paper book or computer memory device from any book or text
13 distribution system. The purchase of a book becomes a PAY-PER-READ™ event
14 avoiding the overhead, "middle-men," printing costs, and time delay associated with the
15 current book distribution system. Published material and text such as the President's
16 speech, a new law, a court decision on abortion, or O.J. Simpson's testimony can be
17 made immediately available to the consumer at a nominal fee. Alternatively, books may
18 be made available free to the end use consumer, subsidized by advertisers who sponsor
19 books or embed advertising within the books.

20 The system is a novel combination of new technology involving the television,
21 cable, telephone, and computer industries. It utilizes high bandwidth data transmissions,
22 strong security measures, sophisticated digital switching, high resolution visual displays,
23 novel controls, and user friendly interface software.

24 The primary components of the text delivery system are the subsystem for
25 preparing the text for delivery and the subsystem for receiving and selecting text that was
26 delivered. An embodiment of the system includes additional components and optional
27 features that enhance the system. The system may be configured for use by bookstores,
28 public libraries, schools and consumers. In one embodiment, the system for consumer
29 use is made up of four subsystems, namely: (1) an operations center, (2) a distribution

1 system, (3) a home subsystem including reception, selection, viewing, transacting and
2 transmission capabilities, and (4) a billing and collection system. Alternative
3 configurations of the system are defined to allow for a variety of traditional and non-
4 traditional delivery methods.

5 The operations center performs several primary functions: manipulating text data
6 (including receiving, formatting and storing of text data), security encoding of text,
7 cataloging of books, providing a messaging center capability, and performing uplink
8 functions. In one embodiment, the system delivers the text from the operations center to
9 consumer homes by inserting text data within analog video signals. The insertion of text
10 is generally performed with an encoder at an uplink site that is within or near the
11 operations center. The system can use several lines of the Vertical Blanking Interval
12 (VBI), all the lines of the analog video signal, a digital video signal or unused portions
13 of bandwidth to transmit text data. Using the VBI delivery method, the top ten or twenty
14 book titles may be transmitted with video during normal programming utilizing existing
15 cable or broadcast transmission capability without disruption to the subscriber's video
16 reception. Using the entire video signal, thousands of books may be transmitted within
17 just one hour of air time. Nearly any analog or digital video or data distribution system
18 may be used to deliver the text data. The text data may also be transmitted over other low
19 and high speed signal paths including a telephone network (e.g., a public switched
20 telephone network) having a high speed connection such as a digital subscriber line
21 (DSL) connection and the Internet, for example.

22 The home subsystem performs at least four functions: connecting to the
23 distribution system, selecting text, storing text, and transacting through a communicating
24 mechanism. The components of the home subsystem may be configured in a variety of
25 hardware configurations. Each function may be performed by a separate component, the
26 components may be integrated, or the capability of existing cable set top converter boxes,
27 computers, and televisions may be utilized. A connector, library unit and viewer unit
28 may be used. In one embodiment, the connector portion of the home subsystem receives
29 an analog video signal and strips or extracts the text from the video. The home library

1 stores the text signal, provides a user friendly software interface to the system and
2 processes the transactions at the consumer home. The viewer provides a screen for
3 viewing text or menus and novel user friendly controls. Alternative embodiments are
4 presented that support delivery of text using a variety of communication mechanisms.

5 The viewing device may be a portable book shaped viewer which stores one or
6 more books for viewing and provides a screen for interacting with the home library unit.
7 A high resolution LCD display is used to both read the books and to interact with the
8 home library software. In one embodiment, an optional phone connector or return-path
9 cable connection initiates the telephone calls and, with the aid of the library, transmits the
10 necessary data to complete the ordering and billing portion of the consumer transaction.
11 Alternative embodiments are presented that support ordering and billing using a variety
12 of communication mechanisms. The user friendly controls include a bookmark, current
13 book and page turn button. The billing and collection system performs transaction
14 management, authorizations, collections and publisher payments automatically. A system
15 similar to the system for consumer use may be used in bookstores, schools and public
16 libraries.

17 The system also provides for various electronic commerce features. The viewer
18 displays identification of products or services and permits the user obtain information
19 concerning them or execute purchase requests for them. The system may display related
20 products or services to the user and also target advertising to the particular user. For
21 certain products, the user may obtain a sample of it. For digital products, the user has the
22 option to download the product directly into the viewer or library.

23 Brief Description Of Drawings

24 Figure 1a is a block diagram of the primary components of an electronic book
25 selection and delivery system.

26 Figure 1b is a block diagram of an electronic book selection and delivery system
27 that uses a composite video signal.

28 Figure 2 is a schematic showing an overview of the electronic book selection and
29 delivery system.

1 Figure 3 is a schematic of a delivery plan for the electronic book selection and
2 delivery system.

3 Figure 4 is a block diagram of the operations center.

4 Figure 5a is a flow diagram of processing at the operations center and uplink.

5 Figure 5b is a block diagram of a hardware configuration for an uplink site.

6 Figure 6a is a block diagram of a hardware configuration for a four component
7 home subsystem.

8 Figure 6b is a schematic of a two unit home subsystem.

9 Figure 7 is a flow diagram of processes performed by a video connector.

10 Figure 8 is a block diagram for an example of a library unit.

11 Figure 9 is a flow diagram of processes performed by a library unit on the
12 received data stream.

13 Figure 10 is a flow diagram of processes performed by a library unit on
14 information requests from a viewer.

15 Figure 11 is a block diagram showing the components for an example of a viewer.

16 Figure 12 is a flow diagram of processes performed by a viewer on an information
17 request from a subscriber.

18 Figure 13 is a chart depicting a menu structure and sequencing of menus in a
19 menu system.

20 Figure 14a is a schematic of an introductory menu.

21 Figure 14b is a schematic showing an example of a main menu.

22 Figures 14c, 14d, 14e, 14f, 14g, 14h, 14i and 14j are schematics showing
23 examples of submenus.

24 Figure 15 is a schematic diagram of an electronic book system for a bookstore or
25 public library.

26 Figure 16a and Figure 16b are schematics of hardware modifications or upgrades
27 to a set top converter.

28 Figure 17 is a schematic showing a set top terminal that includes a data receiver
29 and data transmitter.

Figure 18a is a schematic of a book-on-demand system.

Figure 18b is a schematic of an operations center supporting a book-on-demand system.

Figure 19 is a diagram of a digital television program environment.

Figure 20 is a flowchart of steps involved in processing text at an operations center.

Figures 21a-21g are diagrams of remote location reception options.

Figure 22 presents a hardware configuration of a home subsystem used to receive a program broadcast.

Figure 23 is a flowchart of processes performed by a digital television program connector.

Figure 24a-24c are examples of order systems for use in the broadcast environment of Figure 19.

Figure 25 is a flowchart showing steps associated with ordering over the Internet.

Figure 26 is a diagram depicting components used for delivery of electronic books over the Internet.

Figure 27 presents embodiments for delivery of electronic books using a cable system.

Figure 28 presents embodiments for delivery of electronic books using a wireless broadcast system.

Figure 29 presents embodiments for delivery of electronic books using a satellite broadcast system.

Figure 30 presents embodiments for delivery of electronic books using a wired data network.

Figure 31 presents embodiments for delivery of electronic books using the PSTN.

Figure 32 presents embodiments for delivery of electronic books using a wireless PCS network.

Figure 33 shows a storage device that stores a portable storage medium containing an electronic book.

1 Figure 34 is a block diagram of an alternate system for requesting and delivering
2 electronic books.

3 Figure 35 is a flow chart of a method for providing functions for electronic
4 commerce in conjunction with display of an electronic book.

5 Figure 36 is a schematic illustrating a viewer having selections providing for
6 electronic commerce.

7 Figure 37 is a flow chart of a method for displaying product or service
8 information concerning products or services selected by a user.

9 Figure 38 is a schematic illustrating display of product or service information.

10 Figures 39a and 39b are a flow chart of a method for permitting a user to purchase
11 a product or service.

12 Figure 40 is a schematic illustrating an electronic order form for permitting a user
13 to submit a request to purchase a product or service.

14 Figure 41 is a flow chart of a method for recording statistics concerning requests
15 to purchase or view information concerning products and services.

16 Figure 42 is a flow chart of a method for providing a user with a sample
17 concerning a product or service.

18 Figure 43 is a schematic illustrating a screen for displaying a sample concerning
19 a product or service.

20 Figure 44 is a flow chart of a method for providing a user with an electronic
21 catalog identifying products or services.

22 Figure 45 is a schematic illustrating display of an electronic catalog.

23 Figure 46 is a method for permitting a user to access and use a web browser in a
24 viewer for presenting an electronic book.

25 Figure 47 is a schematic illustrating display of a web browser within a viewer.

26 Figure 48 is a method of retrieving and displaying web pages as selected by a
27 user.

Detailed Description Of Invention

Figure 1a shows an electronic book distribution system 100 that may be used for distributing an electronic book. A content provider 110 may publish hard copy versions of books or other printed media including newspapers, magazines, and product catalogs, for example. The content provider 110 may convert printed materials to an electronic format and provide the electronic formatted materials to a distribution point, or center 120, over uplink path 115. The uplink path 115 may be a wired or a wireless path. The uplink path 115 may be a telecommunications network, for example. The uplink path 115 may be a satellite relay path or a wireless telephone path. The uplink path 115 may involve providing electronic books to the distribution center on a fixed media, such as a CD-ROM, for example.

In Figure 1a, the content provider 110 and the distribution center 120 are shown as separate components of the electronic book distribution system 100. However, the content provider 110 and the distribution center 120 may be co-located.

The distribution center 120 may convert printed matter into an electronic format. Alternately, the distribution center 120 may receive electronic files from an outside source, such as the content provider 110. The distribution center 120 may process and store electronic books.

The distribution center 120 distributes electronic books. The distribution may be, for example, over distribution path 125, distribution network 130, and distribution path 135 to an electronic book subsystem or terminal 140, which may include an electronic book viewer (not shown). The terminal may also be a television, a set top terminal, a personal computer, or similar device. An apparatus and method for distributing electronic books is disclosed in greater detail later. The distribution network 130 may be an electronic book store, an Internet web site, a wired or wireless telecommunications network, an intranet, a radio program delivery system, a television program delivery system, including cable television, satellite television broadcast, and over-the-air broadcast, for example. The electronic book distribution network 130 could include

1 direct delivery through a mail delivery system of electronic books on a fixed media, such
2 as a CD-ROM, for example.

3 Figure 1b shows components of an electronic book distribution system 170 using
4 a television program delivery system to distribute electronic books.

5 In the embodiment shown in Figure 1b, the components of the electronic book
6 selection and delivery system 170 are an encoder 174, a video distribution system 178,
7 a connector 182, and a text selector 186. The encoder 174 places textual data on a video
8 signal to form a composite video signal. Although the composite signal may contain only
9 textual data, it usually carries both video and textual data. A variety of equipment and
10 methods may be used to encode text data onto a video signal. The video distribution
11 system 178 distributes the composite video signal from the single point of the encoder
12 174 to multiple locations, which have connectors 182. The connector 182 receives the
13 digital or analog video signal from the video distribution system 178 and separates, strips
14 or extracts the text data from the composite video signal. If necessary, the extracted text
15 data is converted into a digital bit stream. The text selector 186 works in connection with
16 the connector 182 to select text.

17 Using the connector 182 and text selector 186 combination, various methods of
18 selecting and retrieving desired text from a composite or video signal are possible. Text
19 may be preselected, selected as received or selected after being received and stored. One
20 method is for the connector 182 to strip or extract all the text from the video signal and
21 have the text selector 186 screen all the text as received from the connector 182. The text
22 selector 186 only stores text in long term or permanent memory if the text passes a
23 screening process described below.

24 Figure 2 shows another embodiment of an electronic book selection and delivery
25 system 200. The delivery system 200 includes: an operations center 250 including an
26 uplink site 254, a video distribution system 208, an electronic book device, or home
27 system 258 including a video connector 212, a library 262, a viewer 266, and a phone
28 connector 270, telephone system 274, an Internet web site 279 and a billing and
29 collection system 278. Also as shown in Figure 2, the home system 258 may include

1 connections to a television 259 and a personal computer 261 may be used to display
2 menu screens, electronic books, electronic files, or any other information associated with
3 the electronic book delivery system 200. In addition, the television 259 and the personal
4 computer 261 may provide control functions that replicate and supplement those of the
5 viewer 266.

6 The operations center 250 receives textual material from outside sources 282 such
7 as publishers, newspapers, and on-line services. Alternately, the outside sources may
8 maintain electronic books at the Internet web site 279. The outside sources 282 may
9 convert textual and graphical material to digital format, or may contract with another
10 vendor to provide this service. The operations center 250 may receive the textual and
11 graphical material in various digital formats and may convert the textual material to a
12 standard compressed format for storage. In so doing, the operations center 250 may
13 create a pool of textual material that is available to be delivered to the home system 258.
14 The textual material may be grouped by books or titles for easy access.

15 As used herein, "book" means textual or graphical information such as contained
16 in any novels, encyclopedias, articles, magazines, newspapers, catalogues, periodicals,
17 or manuals. The term "title" may represent the actual title assigned by an author to a
18 book, or any other designation indicating a particular group, portion, or category of
19 textual information. The title may refer to a series of related textual information, a
20 grouping of textual information, or a portion of textual data. For example, "Latest
21 Harlequin Romance", "Four Child Reading Books (Ages 10-12)," "Encyclopedia
22 'BRITANNICA'™," "President's Speech," "Instruction Manual," "Schedule of 4th of
23 July Events," "Pet Handbooks," "Roe v. Wade," and "The Joy of Cooking," are suitable
24 titles. Also, the title may be a graphical symbol or icon. Thus, a picture of a wrench may
25 be a title for a repair book, a picture of a computer a title for a computer book, a graphical
26 symbol of a telephone a title for a telephone book, a drawing of a dagger a title for a
27 mystery book, a picture of a bat and ball a title for a sports book, and a picture of
28 tickertape a title for a business book.

1 The operations center 250 includes the uplink site 254 for placing the text onto
2 a telecommunications signal and sending the telecommunications signal into a
3 distribution system. The uplink site 254 would generally include an encoder 204 (not
4 shown in Figure 2) to encode the text onto the telecommunications signal.

5 Many analog and digital video distribution systems may be used with the
6 electronic book delivery system 200, such as cable television distribution systems,
7 broadcast television distribution systems, video distributed over telephone systems, direct
8 satellite broadcast distribution systems, and other wire and wireless video distribution
9 systems. Nearly any distribution system which can deliver a telecommunications signal,
10 including a video signal, will work with the electronic book delivery system 200. It is
11 also possible to distribute the electronic book without using a telecommunications signal
12 as described in the embodiments presented in Section VII below.

13 The home system 258 performs five functions: (1) connecting with a video
14 distribution system; (2) selecting data; (3) storing data; (4) displaying data; and (5)
15 handling transactions. An important optional function of the home system 258 is
16 communicating using, in one embodiment, a telephone communication system 274. The
17 home system 258 may be made up of four parts: a video connector 212 or similar type
18 of connector for connecting with the distribution system 208, a library 262 for storing and
19 processing, a viewer 266 for viewing menus and text and a telephone connector 270 for
20 connecting with a telephone communications system 274. Additional embodiments are
21 presented in Section VII that address alternative communication mechanisms.

22 The billing and collection system 278 may be co-located with the operations
23 center 250 or located remote from the operations center 250. The billing and collection
24 system 278 may be in communication with the home system 258 using telephone-type
25 communication systems (for example 274). Any of a number of communication systems
26 as presented in Section VII, such as a cellular system or the Internet, will operate with the
27 billing and collection system 278. The billing and collection system 278 records the
28 electronic books or portions of text that are selected or ordered by the subscriber. The
29 collection system will charge a subscriber's credit account or bill the subscriber. In

1 addition, the billing and collection system 278 may monitor that amount due to publishers
2 or other outside sources 282 who have provided textual data or other services such as air
3 time to enable the text delivery system 200 to operate.

4 Also shown in Figure 2 is an intranet 279'. The intranet 279' may be used as a
5 part of a private distribution network for distributing and circulating electronic books.
6 For example, a university library may use the intranet 279' to circulate electronic books
7 to university students and professors.

8 Figure 3 is an expanded overview of a delivery plan 301 for the electronic book
9 delivery system 200. It is a comprehensive delivery plan 301 to support various types of
10 users and various billing systems. Figure 3 shows that publishers 282 may provide text
11 transfer 302 to the operations center 250' and receive payments 306 from the billing and
12 collection system 278'. A separate channel uplink site 254' is shown in this
13 configuration receiving data 310 from the operations center 250'. The operations center
14 250' has three separate sections (318, 322, 326) one for text receiving, formatting and re-
15 entry 318, a second for security encoding 322 and a third section for catalog and
16 messaging center functions 326.

17 The collection and billing system 278' shown has two sections (330, 334) one for
18 transaction management, authorizations and publisher payments 330, and the other for
19 customer service 334. The customer service section 334 provides for data entry and
20 access to customer account information. Transaction accounting information 338 is
21 supplied to credit card companies 342 by the transaction management section 330 of the
22 billing and collection system 278'. The credit card companies 342 provide billing 346
23 to customers either electronically or by mail.

24 Methods for communicating between the subscriber base 348 and the billing and
25 collection system 278' include: by telephone switching 350 alone, cellular switching 354
26 and telephone switching 350 combined, and by use of the cable system 358 and the
27 telephone switching 350. The system shown supports both one-way 362 and two-way
28 cable communication 366 with subscribers. Additional communication methods are

1 presented in Section VII. Public libraries and schools 370 as well as bookstores 374 may
2 use the delivery system 301.

3 Public libraries and schools 370 could have a modified system to allow the viewer
4 to be checked-out or borrowed while bookstores 374 would rent or sell the viewer and
5 sell electronic book data. The bookstores 374 as well as the public libraries and schools
6 370 may be serviced by cable 378. Optional direct broadcast systems (DBS) 382 can also
7 be used with the system 200 as detailed in Section VII.

8 I. The Operations Center

9 Figure 4 is a schematic of the operations center 250, which includes the uplink
10 254. The operations center 250 may gather text or books by receiving, formatting,
11 storing, and encoding. A data stream 302 containing text may be received at the
12 operations center 250 by a data receiver 402. The data receiver 402 is under the control
13 of a processor 404. After reception, the data stream is formatted using digital logic for
14 formatting 406 which is also under the control of the processor 404. If any additional text
15 is generated at the operations center 250 locally for insertion into the distributed signal,
16 the text generation is handled through text generator hardware 410, which may include
17 a data receiver and a keyboard (not shown). Following processing by the text generator
18 410, the additional text can be added to the text received by the combining hardware 414
19 that includes digital logic circuitry (not shown).

20 The processing at the operations center 250 is controlled by a processor 404,
21 which uses an instruction memory 416. The processor 404 and instruction memory 416
22 may be supplied by a personal computer or mini-computer, for example. To perform the
23 catalog and messaging functions, the operations center 250 uses a catalog and message
24 memory 420 and the text generator 410 if necessary.

25 The data stream of text, catalog and messages may be encoded by security module
26 encoding 424 prior to being sent to the uplink module 254. Various encoding techniques
27 may be used by the security encoding module 424 such as the commercial derivative of
28 NSA's encryption algorithm (Data Encryption System (DES)) and General Instrument's
29 DigiCipher II. Following encoding, the encoded text may be stored in text memory 428

1 prior to being sent to the uplink 254. A first-in-first-out text memory arrangement may
2 be used under the control of the processor 404. Various types of memory may be used
3 for the text memory 428 including RAM. The operations center 250 may use file server
4 technology for the text memory 428 to catalog and spool books for transmission as is
5 described below. The operations center 250 may also store the electronic book as
6 compressed data files.

7 In an embodiment, to transmit textual data, the distribution system 208 (see
8 Figure 2) may use high bandwidth transmission techniques such as those defined by the
9 North American Broadcast Teletext Standard (NABTS) and the World System Teletext
10 (WST) standard. Using the WST format (where each line of the Vertical Blanking
11 Interval contains 266 data bits), a four hundred page book, for example, may be
12 transmitted during regular television programming using four lines of the Vertical
13 Blanking Interval at a rate of approximately one book every 1.6 minutes (63,840 bits per
14 second). Alternatively, books may be transmitted over a dedicated channel, which
15 interrupts programming so that 246 lines of video can be used to transmit approximately
16 2,250 books every hour (3.9 Mbits per second). A teletext type format is the simplest but
17 possibly the slowest text format to use with the electronic book delivery system 200. In
18 either event, an encoder 204 may be used at an uplink site 254 to insert textual data into
19 the analog video signal. In many other respects, the delivery of the textual information
20 may be completed using an existing cable television plant and equipment. Alternative
21 transmit formats and delivery systems are presented in Section VII.

22 Figure 5a is a flowchart of steps involved in processing text from the publisher
23 or provider 282 that may occur at the operations center 250. As shown in block 500, the
24 publisher 282 processes data files of text for books, compresses, encrypts and sends the
25 data files to the operations center 250 or uplink 254. Text files for books may be sent one
26 book at a time. As shown in block 504, the uplink 254 or operations center 250 receives
27 and processes the data stream from the publisher 282. Generally, part of this processing
28 includes encryption and error correction. Text files may be delivered for receipt by
29 multiple home subsystems simultaneously, or to a specific individual home subsystem.

1 In Figure 5a, the electronic books are distributed to consumers using a video
2 distribution system such as a cable television system. However, the electronic books may
3 also be packaged as data packets and distributed over other telecommunications networks
4 such as a digital wireless telephone network, for example.

5 In one embodiment, as shown in block 508, files are broken into smaller packets
6 of information. Header information is added to the packets. The bit stream is converted
7 from a serial digital bit stream to an analog bit stream that is compatible with an NTSC
8 video signal. Block 512 shows the switching of analog data into the video lines of a
9 video signal. The analog data may be placed either in the VBI or the active video lines.
10 In some instances, unused portions of bandwidth (such as 5-40 MHZ, 70-75 MHZ, 100-
11 109 MHZ or other guard bands) may be used instead of the video lines. Alternate
12 transmission methods are presented in Section VII.

13 Figure 5b is an example of a hardware configuration to perform some of the
14 functions for blocks 508 and 512. A video feed 516 is received and processed through
15 a sync stripper 520. The stripped sync signal 532 is used by the digital logic control 524.
16 The digital logic control 524 receives the sync signal 532 and a serial digital bit stream
17 528 for processing. The digital logic control 524 passes the serial digital bit stream to the
18 Digital to Analog converter 536 and outputs a control signal 540 for the video switch
19 544. The video switch 544 integrates the video feed 516 and analog data stream 548 into
20 a video feed with analog data signal inserted 552.

21 As an alternative to cable, broadcast or other television delivery methods, the
22 public telephone system may be used to transmit books to the subscribers. An average
23 book would take about 7 minutes to transmit over the public telephone system. Using the
24 telephone system, it is not necessary to combine video and text into a composite signal.
25 In most other respects, the operations center would remain similar whether text delivery
26 was by telephone or cable. File server technology (such as that described in U.S. Patent
27 No. 5,262,875, entitled AUDIO/VIDEO FILE SERVER INCLUDING DECOMPRESSION/
28 PLAYBACK MEANS, issued to Mincer, et al., and, U.S. Patent No. 5,218,695, entitled FILE
29 SERVER SYSTEM HAVING HIGH-SPEED WRITE EXECUTION, issued to Noveck, et al.,

1 incorporated herein by reference) may be used at the operation center with a telephone
2 system text delivery method.

3 As another alternative to cable, television, and telephone system delivery, the
4 public telephone system may be used to provide access to the Internet, where the Internet
5 web site 279 may be accessed. Electronic books may be ordered, paid for, and delivered
6 directly from the Internet web site 279 over the telephone system.

7 When a wireless telephone network is used to distribute electronic books, or
8 otherwise communicate with the home system 258, the home system may receive data
9 using any one or more standard protocols including time division multiple access
10 (TDMA), code division multiple access (CDMA), Global Systems for Mobile
11 Communications (GSM) and Advanced Mobile Telephone System (AMPS) protocols.

12 In any delivery system using the telephone system, individual subscribers may
13 increase the electronic book deliver rate by incorporating high speed modems or other
14 communications devices such as an Integrated Services Digital Network (ISDN)
15 connector, or by use of a Digital Subscriber Line (DSL). These alternative delivery
16 methods are presented in Section VII.

17 II. The Home Subsystem

18 The hardware configuration for a four component home system 258 is shown in
19 Figure 6a. Figure 6b shows a hardware configuration for a two component home
20 subsystem. The home system 258 performs several functions, such as receiving data and
21 video transmissions, stripping (or extracting) the data from the video signal, screening
22 and storing the data, providing user friendly interface controls and software, displaying
23 menus and text, processing transactions, initiating telephone calls and transmitting billing
24 data. Various hardware configurations may be utilized to achieve the desired functions
25 of the home system 258. For example, as shown in figure 6b, the home system 258 can
26 be configured to utilize the reception and channel tuning capability of the current
27 installed subscriber base of cable converter boxes and televisions 601 and networked
28 computers. The home system 258 can also be designed as an advanced set top terminal
29 converter box with menu generation capability, electronic memory and a telephone

1 modem as described in section V below. Alternatively, the home system 258 can be
2 configured to support alternate delivery and ordering methods as described in Section
3 VII.

4 The electronic components, which make up the home system 258 can be arranged
5 in a variety of ways. In the four unit subsystem of figure 6a the viewer 266 and library
6 262 are wired together while the remaining components communicate through RF
7 transceivers 604. In a simple version of the home system 258 there are only two units,
8 a library 262 and a viewer 266. Figure 6b shows a two unit home system 258 with certain
9 optional features.

10 The viewer 266 is generally equipped with a high resolution viewing area 602,
11 digital logic (including a key 605, security 606, and a microprocessor 621), video
12 graphics control and memory 607, power supply circuitry 602 (not shown), an optional
13 battery 603 and an optional RF transceiver 604. In a two unit arrangement, the library
14 262 contains the connector function to the electronic book distribution system 208,
15 connector function to a public telephone communications system, and memory 600
16 (which may be removable and portable 600'). More specifically, the library 262 would
17 include data stripping functions 617, digital logic 609, memory storage 600, power
18 circuitry 610, optional connections 611 (including cellular or PCN 611'), optional battery
19 (not shown), optional tuner module 613 and an optional RF transceiver 604. The
20 connector 212 and the public telephone system connection 270, as well as the removable
21 portable memory unit 600 of the library 262 may be broken out into separate components.
22 (Figure 6b shows a removable portable hard disk memory 600' with removable cartridges
23 614.) Finally, the home system 258 may include an attached keyboard 267 or a wireless
24 keyboard 268. Both the attached keyboard 267 and the wireless keyboard 268 may be
25 used to communicate with the viewer 266 (not shown) or the library unit 262. The
26 wireless keyboard 268 may communicate using radio frequency (RF) signaling, for
27 example.

28 In an alternate arrangement, all functions of the home system 258 may be
29 incorporated into a single unit. The functions of the library 262, for example, may be

1 carried out by a card or chipset in the viewer 266. All the communications devices
2 needed to couple the home system 258 to various telecommunications networks may also
3 be incorporated into the viewer. All interfaces between the home system 258 and the
4 subscriber may be included with the viewer 266. In this embodiment, the viewer 266
5 may include a communication device for receiving inputs from a separate keyboard. The
6 viewer 266 may also include a built-in video camera 608" that may be used to transmit
7 images of the subscriber. Using the transceiver 608, the camera 608" and the
8 speaker/microphone 608', the subscriber may use the viewer 266 for video conferencing,
9 for example.

10 Therefore, the home system 258 may have as many as five separate components,
11 which communicate with each other. The two, three, four or five separate components
12 which make up the home subsystem can communicate with each other in a variety of
13 ways, including hardwired connection 615, RF transceiver 604 and other wireless
14 methods.

15 RF communications may be used in the home, allowing separate components to
16 be located throughout the home without restriction. The data communicated between the
17 units may be secure data. In addition, the library 262 may provide power to the viewer
18 266 through the hard wire communication link 615.

19 To receive and strip data from a video signal at the consumer's home, a device
20 such as a cable interface device or cable connector 212 is used. The cable connector
21 device includes a tuner 613, while the cable interface device makes use of existing tuning
22 equipment in the home. In either configuration, data is stripped from the video signal
23 and stored at the subscribers location in the library 262. The phone connector 270,
24 optional connector 611, and modular connector 701 initiate communications and transmit
25 ordering and billing information to the operations center 250 or billing and collection
26 system 278. A digital connector 619 is provided to communicate digital information with
27 the set top 601. The library 262 is the intelligent component of the home subsystem,
28 incorporating the hardware and software necessary to store the text data, generate menus
29 and effect the purchase transactions. In addition to an RF transceiver 604, the home

1 library 262 also includes the necessary jacks and connections to allow the system to be
2 connected to the viewer 266. As shown in Figure 6b, the library 262 communicates the
3 text data to the viewer 266 in a secure format, which requires a key 605 for decryption.
4 The text may be decrypted page by page just before viewing.

5 a. The Video Connector

6 Figure 7 shows the flow of the processes performed by the video connector 212.
7 The video connector 212 receives the video signal 608, tunes to the channel containing
8 the text data 612, strips the text data from the video signal 616, and communicates the
9 text data stream to logic components in the library 620.

10 The connection to the video distribution system may be a cable connector to a
11 cable television delivery system, as shown in Figure 6b. The cable connector includes
12 a data stripper circuit 617, which accepts video input from either a set top converter, TV
13 or VCR 601, or an optional tuner block 613 that receives the CATV signal through the
14 cable connector 212'. The data stripper circuit 617 strips data out of the video, and
15 outputs a digital bit stream to the digital logic portion 609 of the library unit 262. The
16 data is embedded in the video signal either in the vertical blanking interval or the active
17 video portion in an encrypted and compressed format. The data stripper circuit 617 can
18 be placed inside the set top converter box 601, TV, or in the library unit. The data
19 stripper circuit 617 outputs the digital bit stream to be used by the library digital logic
20 609.

21 The video connector 212 may also contain a channel tuner module 613 that can
22 tune to the video channel and provide access to the video that contains the data to be
23 stripped. Using the optional tuner module 613, a set top converter, VCR, or TV tuner is
24 not needed in the home subsystem. The optional tuner module 613 would instead receive
25 the CATV signal directly through the cable connector 212. Additional connector options,
26 which allow for the receipt of text files using alternative delivery methods, are presented
27 in Section VII. This ubiquitous access is provided using the modular connector 700 as
28 depicted in Figure 6b.

1 b. Library

2 An embodiment of the library 262 for a two unit home subsystem is shown in
3 both Figure 6b and Figure 8. The embodiment shown includes the following optional
4 parts: the video connector 212, phone connector 270, RF transceiver 604, and battery
5 pack 624 in addition to a removal portable memory 600', microprocessor 628, instruction
6 memory unit 632, digital logic 636, and power unit 640.

7 The library 262 contains a digital logic section 609 (not shown in Figure 8) which
8 includes the microprocessor 628, the digital logic 636 and the instruction memory unit
9 632. The microprocessor 628 may be a secure microprocessor such as the Mot SC21
10 device sold by Motorola. The digital logic section 609 will receive the serial digital bit
11 stream from the data stripper circuit 617 and process the data. Error correction will also
12 be performed by the digital logic section 609 and the data will be checked for proper
13 address. If the address of the data is correct and the library 262 is authorized to receive
14 the data, the data will be transferred to the memory storage unit 600, 600'. Authorization
15 to receive the data is provided by the cable headend or another distribution point. An
16 authorization code may be sent in the serial digital bit stream. The digital logic section
17 609 will send appropriate text and graphical data to the memory storage unit 600, 600'.
18 It transfers this data in a compressed and encrypted format and the data remains stored
19 in a compressed and encrypted format.

20 i. Memory Storage Unit

21 The memory storage unit of the library may be a removable portable memory unit
22 600' (as shown in Figures 6a, 6b and 8). A variety of options are available for memory
23 storage: a hard disk drive, such as an 80 megabyte, a 200 megabyte, a hard disk with
24 removable platters, and CD ROM. Referring to Figure 6b, a hard disk drive unit 600',
25 which contains removable platters, may also be used. This would provide virtually
26 unlimited library storage capacity. Data will be stored in the memory storage unit in a
27 compressed and encrypted format. As is also shown in Figure 6b, the data may also
28 contain a key or unique ID number that matches the ID or key of the viewer 266. This
29 matching of a unique key or ID number prevents unauthorized transfer of text data from

1 the memory storage unit to an unauthorized viewer. Small memory devices such as smart
2 cards, electronic memory cards or PCM CIA cards (personal computer memory card
3 industry association) may also be used to store the data.

4 ii. Power Circuitry

5 As shown in figures 6b and 8, the library 262 will accept power from AC wall
6 power 610, DC power 640, or optional battery power 624. The power circuitry 610, 640
7 may provide all the voltage necessary from either the battery 624 or AC unit for the
8 various circuitry in the library. The power circuitry 610, 640 may also provide power to
9 the viewer through a single data cable when connected to the viewer. The power circuitry
10 610, 640 will recharge the battery using AC power when in operation. With the optional
11 battery unit 624 installed, the library 262 becomes a portable unit and can still provide
12 power to the viewer 266. In order to extend battery life, power conservation measures
13 may be utilized, such as shutting down the memory system when not in use. When the
14 viewer unit 266 is being utilized and the library circuitry is not being utilized, virtually
15 all power may be shut down to the library 262.

16 iii. Connection to the Public Telephone System

17 In an embodiment, the connection to the telephone system may be provided by
18 a connector device 611, which consists of a modem. Various available modems may be
19 used to perform this function. As shown in Figure 6b, cellular phone or PCN phone
20 connections 611' may also be provided. When the home system 258 is first initialized,
21 the modem may be used to transfer the name and credit card information of the consumer
22 to the billing and collection system 278. The telephone connection 270 may be utilized
23 each time an electronic book is purchased by a consumer to complete and record the
24 transaction. The telephone connection 270 may also be used to receive the text data from
25 the operations center 250, by-passing the video distribution system 208. The phone
26 connection 270 may be a separate unit as shown in Figure 6b. However, alternate means
27 exist to connect the home system 258 to the billing and collection system 278 or the
28 operation center 250. The modular connector 701 (shown in Figures 6b and 8) provides
29 access to each communication network to provide a path from the home system 258 to

1 the billing and collection system 278 or the operations center 250. These alternatives are
2 presented in detail in Section VII.

3 iv. Library Processing

4 Figure 9 shows for one embodiment, an example of processing performed by the
5 digital logic section 609 of the library 262 on the data stream 651 received from the video
6 connector 212 or stripper circuit 617. In step S650, digital logic section 609 checks the
7 data stream 651 for error correction. If an error is detected, in step S654 digital logic
8 section 609 de-interleaves the data and in step S658 runs a FEC (Forward Error
9 Correcting) algorithm. In steps S650, S654 and S658, the digital logic section 609
10 performs the error correction needed on the data stream. If no error correction is
11 necessary the digital logic section 609 proceeds to step S662 and checks data packets
12 individually for packet address.

13 If the address is a unique address, the process moves to step S666 and the digital
14 logic section 609 checks whether the address of the packet matches the library box ID
15 number. The library box ID number is a unique number associated with the library 262.
16 The library box ID is used to ensure security of the data. The process then moves to step
17 S670 and the digital logic section 609 determines whether an electronic file has already
18 been opened into which the data packet can be saved. If no data file has been opened, the
19 digital logic section 609 opens a new data file for that packet. If an electronic file has
20 been opened, the process moves to step S678 and the digital logic section 609 saves the
21 packet in the electronic file on disk. The process moves to step 682 and the digital logic
22 section 609 checks to see if this is the last packet for a particular book for a particular
23 textual data block being received. If it is the last packet of information, the process
24 moves to step 686 and the digital logic section 609 closes the electronic file and updates
25 the directory of available electronic files. Following either step S682 or S686, the
26 process returns to receive another data packet from the data stream received from the data
27 stripper block.

28 If the packet address is checked and the address is determined to be a broadcast
29 address, the process moves to step S690 and the digital logic section 609 determines the

1 type of message that is being sent. The message may be an index of book titles, menu
2 (and menu graphics) information, announcements, special offerings, discounts,
3 promotions, and previews, for example. The process then moves to step S694 and the
4 digital logic section 609 stores the message in an appropriate electronic message file.
5 The process then returns to step S650 to receive another data packet and perform another
6 error check.

7 Using the process of Figure 9, the library 262 is able to receive, store and update
8 directories related to the textual data and graphical data (that can be used to depict
9 pictures in a given book or to generate menus). Variations of the processes are possible
10 depending on the format of the data and operating system of the library 262.

11 Figure 10 shows an example of the processing of information requests from the
12 viewer 266 at the library 262. Information requests from the viewer 266 are received
13 either through the cable connecting the viewer 266 to the library 262 or through wireless
14 transmissions such as RF. It is possible in some embodiments for subscribers' requests
15 to come from a set top converter box 602 (see Section V).

16 Information requests received from the viewer 266 generally fall into three
17 categories: (1) directory data of books stored in the library 262, (2) index of all available
18 books on the system, and (3) requests for a specific book (step S700). In step S704, the
19 digital logic section 609 answers a request from the viewer 266 for a directory of data
20 showing the books stored at the viewer 266. The directory of data is sent to the viewer
21 266 so that it may be displayed to the subscriber. In step S708, the digital logic section
22 609 handles requests from the viewer 266 for an index of all available books on the
23 system. The library 262 will obtain an index of all the available books on the system and
24 transmit that index, in step S712, with menu information to the viewer 266. In step S716,
25 the digital logic section 609 replies to a request from the viewer 266 for a specific book.
26 In step S720, the digital logic section 609 opens an electronic file for the specific book
27 requested by the viewer 266 and transmits the record or transmits the information on a
28 packet-by-packet basis to the viewer 266. This process of transmitting the specific book,

1 record, or packets to the viewer 266 continues until the last record or packet has been sent
2 in step S724.

3 In addition to the processes shown on Figure 10 in handling a request for a
4 specific book, the library 262 also orders and receives specific books from the operations
5 center 250 using the process as described in step S716. Following a request for a specific
6 book which is not stored at the library 262, the library 262 will proceed to determine the
7 next available time the book will be on the video distribution system 208 or an alternative
8 delivery system and ensure reception and storage of that book (process not shown). In
9 performing this process the library 262 will transmit to the viewer information on when
10 it will obtain the text data for the book so that the subscriber may view the book. In
11 addition to timing information, price and other ordering information may also be passed
12 by the library 262 to the subscriber.

13 c. The Viewer

14 Figure 11 is a block diagram of a viewer 266 showing its internal components.
15 The viewer 266 of Figure 11 is similar to the viewer 266 depicted in Figure 6b. The
16 viewer 266 is designed to physically resemble a bound book. The viewer 266 is made
17 up of five primary components and seven optional components: (1) LCD display 602,
18 (2) digital circuitry (not shown), (3) video graphics controller 607', (4) controls 740, (5)
19 book memory 728, (6) optional power supply circuitry 736, (7) optional battery 603', (8)
20 optional RF transceiver 604, and (9) optional cellular or mobile connector (such as 611')
21 (10) optional keyboards 267 and 268, and (11) an optional speaker/microphone 608',
22 (12) optional alternative communication interface devices.

23 (1) A high resolution LCD screen 602, of VGA quality, may be used by the
24 viewer 266 to display text and graphic images. The screen may be the size of one page
25 of an electronic book. A two page screen or two screens may also be used with the
26 viewer 266.

27 (2) Digital circuitry that includes a secure microprocessor 621, instruction
28 memory 732, and digital logic. Data is transferred to the viewer 266 in compressed and
29 encrypted format. The secure microprocessor 621 compares the ID number of the viewer

1 266 with the incoming data stream and only stores the text data if the ID number of the
2 viewer 266 matches that within the incoming data stream. The viewer 266 may be
3 configured to not output text data or other data and that the data is decompressed and
4 decrypted only at the moment of viewing and only for the current page being viewed.
5 These measures provide additional security against unauthorized access to data.

6 (3) A video graphics controller 607' that is capable of assisting and displaying
7 VGA quality text and graphic images is included in the viewer 266. The graphics
8 controller 607' is controlled by the digital circuitry described above. Text may be
9 displayed in multiple font sizes.

10 (4) The viewer 266 of Figure 11 has touch panel controls 740. These unique
11 and novel controls 740 allow the consumer to select stored electronic books and
12 electronic books from catalogues, move a cursor, and turn pages in an electronic book.
13 Typically, the controls 740 include forward and reverse page buttons 742, 741, a ball 743
14 for cursor movement, one or more selection buttons 745, a current book button 747 and
15 a bookmark button 749 (see Figure 14a).

16 The controls 740 should be easy to use and conveniently located. Referring to
17 Figure 14a, the controls for the viewer 266 may be located below the screen 602 at the
18 bottom portion of the viewer 266. The next page turn button 742 is the most used button
19 740 and is located towards the right edge of the page. The subscriber is likely to use right
20 hand thumb movements to work the controls particularly the page turn buttons 741, 742.
21 Therefore, the buttons may be arranged in such a manner that the buttons are easily
22 controlled by a subscriber's right thumb. Generally, this can be accommodated either on
23 the lower portion of the viewer 266 (as shown) or along the right hand margin of the
24 viewer 266 (not shown). The current book button 747 and bookmark button 749 are
25 usually the least used of the controls 740. Therefore, in the example shown, those
26 buttons 747, 749 are located on the inside portion towards the binder of the viewer 266.

27 Locating the ball 743 or other cursor movement device (such as four pointer
28 arrows not shown) in the bottom center of the viewer 266 is both easier for the subscriber
29 to use and easier in manufacturing the viewer 266. The selection buttons for the cursor

745 may be located below the middle diameter of the cursor ball 743 on the right and left sides of the ball as shown. If pointer arrows are used for cursor movement, a selection button 745 may be located in the center of the four arrow buttons (not shown). Again, the most used controls 740 should be located where a subscriber's right hand thumb would normally rest.

(5) Book memory 728 for at least one electronic book or more of text is included in the viewer 266. The memory 728 stores text and any graphics, which represent pictures in a book. The memory 728 can also store menu graphics data. Two different memory 728 devices may be used in the viewer 266, one for the instructions for the microprocessor 621 in the digital circuitry and a second type of memory may be used for the book memory 728 (and graphics). Various memory devices available on the market may be used such as, ROM, RAM or a small hard disk. Since an electronic book requires approximately 0.6 megabytes of storage, a small hard disk providing approximately 60 MBytes of storage provides memory to store approximately 100 electronic books.

Text for electronic books may be displayed in various font sizes. To accommodate various fonts for display, a variety of fonts are stored in instruction 732 or book memory 728. Thus larger or smaller fonts may be recalled from memory 621, 728 to create displays desired by the subscriber.

(6) Power supply circuitry 736 in the viewer 266 will accept power from either an AC power source or from an optional battery 603', or the library 262. The power supply circuitry 736 provides the necessary voltages to accommodate the various systems within the viewer 266.

(7) An optional battery 603' is provided in one embodiment. The battery 603' is automatically recharged when AC power is available.

(8) An optional RF transceiver 604 which provided two-way data link between the viewer 266 and other components of the home subsystem can also be included in the viewer 266.

(9) Also, the viewer 266 may include a cellular transceiver (not shown) for mobile communications.

1 (10) The optional wired (attached) keyboard 267 and wireless (e.g., RF)
2 keyboard 268 (see Figure 6a) may be used with the viewer 266 to provide
3 communications between the subscriber and the viewer 266.

4 (11) The optional speaker and microphone 608' allow the viewer 266 to
5 provide audio signals to the subscriber, and allow the subscriber to provide an audio
6 input. The speaker and microphone 608' may be used in conjunction with the cellular
7 transceiver 608 or other telecommunications equipment to provide for reception and
8 transmission of telephony and data.

9 (12) The optional alternative communication interface devices allow the viewer
10 266 to make use of a variety of communication paths.

11 The viewer 266 of Figure 11 has parts available for providing connections to: a
12 library 744, electronic card memory 748, CD ROM units 752, and a portable memory unit
13 756 (such as that shown in Figure 6b as 600'). Various electronic memory cards such as
14 PCMCIA can be used with the viewer 266 to supply and store electronic books.

15 Security, low power consumption and excellent display technology are desired
16 features of the viewer 266 design. The viewer 266 should be lightweight and portable.
17 The viewer 266 contains a software operating system that allows electronic books to be
18 stored, read and erased and includes the capability to order electronic books and retain
19 them in memory 728 for a predefined period of time determined by the system operator.
20 The software can be configured to allow the electronic book to be read during a period
21 of time (i.e., two weeks) and then automatically erased, read once and erased, or held in
22 memory permanently. Each viewer 266 may have a unique key 605. All of the data
23 storage may be encrypted with the key 605 for an individual viewer 266 to prevent more
24 than one viewer 266 accessing the text file or electronic book file.

25 Figure 12 is a flow diagram of some of the processes executed by the
26 microprocessor 621 in the viewer 266. The viewer 266 may receive inputs from the
27 subscriber through touch panel controls 740. In step S800, the subscriber's information
28 requests are then processed by the microprocessor 621.

1 In step S804, if the subscriber requests a menu of available electronic books, the
2 microprocessor 621 will select an electronic book menu. In step S808, the
3 microprocessor 621 will open the electronic files that list the electronic books which are
4 available (related to the category of topic of the menu) and display the menu with the
5 names of the available electronic books.

6 If the subscriber selects a particular book to read, then in step S812, the
7 microprocessor 621 will process the selection and determine the electronic file that
8 contains the specific electronic book. In step S816, the microprocessor 621 will open the
9 file for that specific electronic book and normally access the first page. (If a pointer has
10 already been set in that books electronic file, the process may default to that page.) In
11 step S820, the microprocessor 621 will then determine which page needs to be displayed.
12 That is, the microprocessor 621 will determine whether a next page, previous page or a
13 bookmarked page needs to be displayed. If the pointer for the electronic file is not in the
14 correct location then in step S828, the microprocessor 621 will move the pointer and
15 obtain the previous page of data from the stored file. Otherwise, in step S824, the
16 microprocessor 621 will normally obtain the next page of text from the stored electronic
17 file. In step S832, the microprocessor 621 will decrypt and decompress the text data and
18 send the data to the video display. The video display will generally have a video display
19 memory associated with it. In step S832, the microprocessor 621 will send the data
20 directly to that video display memory. The circuitry for the display then completes the
21 process of displaying the page of text.

22 If the subscriber, through the controls 740, requests (from step S800) that the
23 power be turned off, then in step S836, the microprocessor 621 initiates power off. In
24 step S840, the microprocessor 621 saves the pointer in memory to the page number in the
25 book that the viewer 266 is currently reading. In step S844, the microprocessor 621
26 closes all the electronic files and signals the power circuitry to shut down the power to
27 the various circuits in the viewer 266. With these examples of basic processes the viewer
28 266 is able to display book selections and display text from those electronic books.

d. Menu System

Referring generally to Figure 13, the electronic book system 200 may have a menu system 851 for selecting features and books from the electronic book system 200. The operating software and memory required for the menu system 851 may be located at the viewer 266 (e.g., the instruction memory 732 and/or book memory 728). However, it can also be located at the library 262 (e.g., the instruction memory 632) or the library 262 and the viewer 266 can share the software and memory needed to operate the menu system 851. Since the menus are usually displayed on the viewer, and since the viewer 266 may be capable of operating in the absence of the library 262, the basic software and memory to create the menus is more conveniently located at the viewer 266.

The menu system 851 allows sequencing between menus and provides menu graphics for graphical displays such as on the LCD display 602 of the viewer 266. In an electronic book system that uses a set top converter these menus may also be displayed on a television screen. In an electronic book system that uses a computer, these menus may also be displayed on the computer monitor. In an embodiment, the menus provide just basic text information from which the subscriber makes choices. In other embodiments, the menus provide visual displays with graphics and icons to assist the subscriber and allow for subscriber interaction and real-time ordering of electronic books or other content available to the subscriber.

Figure 13 depicts the menu system 851 with sequencing. The primary menus in the menu system 851 are an introductory menu 850, a main menu 854 and various submenus 858. In the embodiment shown, there are three levels of submenus 858. In certain instances one or two submenus 858 is sufficient to easily direct the subscriber to the selection or information requested. However, there are features in which three or more submenus 858 make the user interface more friendly for the subscriber. Each level of submenus 858 may consist of multiple possible menus for display. The particular menu displayed depends on the selection by the subscriber on the previous shown menu. An example of this tree sequence of one to many menus are the help submenus 887, 888.

1 Depending upon the specific help requested, a different level two help menu is displayed
2 to the subscriber.

3 An example of an introductory menu 850 is shown on Figure 14a. Generally the
4 introductory menu 850 introduces the viewer 266 to the system and provides initial
5 guidance, announcements and instruction. The introductory menu 850 is followed by a
6 main menu 854, an example of which is shown in Figure 14b. The main menu provides
7 the viewer 266 with the basic selection or features available in the system. Figure 14b
8 is an example of a main menu 854 offering many additional features and submenus 858
9 to the subscriber. For example, Figure 14b shows that the viewer 266 is able to choose
10 by a point and click method, many options including: (1) free previews, (2) books you
11 can order, (3) books in your library, (4) your current book, (5) help, (6) on-line services
12 and (6) other system features. Following a selection on the main menu 854, a
13 corresponding submenu 858 is shown.

14 Figure 13 shows fourteen available primary or first level submenus. They are (1)
15 account set up 862, (2) free previews 866, (3) book suggestion entries 855, (4) books in
16 your library 872, (5) books you can order 878, (6) your current book 884, (7) help 887,
17 (8) available features 890, (9) messages 893, (10) account information 896, (11) outgoing
18 message submenu 898, (12) show links submenu 970, (13) create links submenu 980, and
19 (14) show interactive files submenu 990. Figure 14c is an example of a first level
20 submenu for books in your library 872. This "Book In Your Library" example submenu
21 872 shows six available books by title and author and provides the subscriber with the
22 ability to check a different shelf of books 874 or return to the main menu 854. Figures
23 14d and 14e show example submenus 858 for books that may be ordered using the
24 "Books You Can Order" submenu 878.

25 Figure 14f is an example of a confirmation menu which confirms a subscribers
26 order. In this particular example, the subscriber is required to enter a PIN number to
27 complete the subscriber's order. Any alpha-numeric or similar password may be used to
28 ensure the subscriber is an authorized subscriber. In one embodiment, the subscriber

1 confirms an order with a PIN or password and then receives a final confirmation screen.

2 The final confirmation screen is primarily text and may state:

3 **Your book order is now being processed using CABLE.**

4 **Your book will be delivered overnight and your VISA account will be**
5 **charged \$2.95.**

6 **Your book will be available for reading at 6:00AM EST tomorrow. Make**
7 **sure that:**

8 **1. your Library Unit and Cable Connection Unit are plugged in with aerials**
9 **up tonight; and**

10 **2. you tune your cable converter to THE BOOK Channel. The TV set does**
11 **not have to remain on.**

12 or similar language.

13 Examples of the "Account Set Up Menu" 862 and further submenus 858 related
14 to account set up (which provide instructions and account input 864) are shown in
15 Figures 14g and Figure 14h. These submenus 858 allow initialization of an account at
16 the operations center 250 and orders to be charged to credit cards. The submenus 858
17 include the ability to enter data related to your desired PIN number or password, credit
18 cards, phone numbers, etc. In one embodiment, the account set up be performed using
19 the telephone system. A confirmation menu verifies that the account has been properly
20 set up with the desired PIN or password and credit card. However, additional set-up
21 methods are presented in Section VII.

22 Free previews for books 866 are also provided by submenus (868, 870).
23 Examples of the free preview menus are shown in Figure 14i and Figure 14j. Figure 14i
24 shows a menu depicting various books for which previews are available for viewing.
25 Following a book selection, a screen submenu showing an excerpt of the selected book
26 cover's description is provided along with an excerpt from a critic's review of the selected
27 book. In one embodiment, this preview screen for a particular book also allows the
28 subscriber to select a submenu which provides information about the author. The book
29 preview submenu may also include a still video picture or graphics portraying a book

1 cover or a scene from the book. An example of such a still video picture or graphics is
2 shown in figure 14j which depicts a preview screen 870 about the author. The author's
3 preview screen 870 shows a picture of the author, provides a short biography, and may
4 allow the subscriber to order the author's books. The price for ordering the authors
5 various books may also be shown on the menu.

6 In addition to free previews, in other embodiments, the electronic book system
7 200 provides the subscriber with a book suggestion feature (see 855). This is
8 accomplished using the menu system 851 and the processor with associated memory
9 located at the viewer 266, library 262 or at the distribution point (1020 or 250). When
10 necessary, information for the book suggestion feature is sent in the text data of the signal
11 to the home system 258. With this feature, books or authors are suggested to a subscriber
12 based upon historical data of the subscriber's previous orders, demographics or mood of
13 the subscriber, other indicators, and/or by text word searches.

14 In one book suggestion embodiment, text word searches of preview information
15 (such as book cover descriptions, critics reviews and biographies about the author) and/or
16 text of books or other titles are performed by the library 262 using databases stored in the
17 library memory 600. Personalized book or author suggestions are made to the subscriber
18 by obtaining information from the subscriber indicative of general subscriber interests.
19 Subscriber entries may be solicited from the subscriber using the book suggestion entry
20 submenu 855. The system uses these subscriber entries either directly or indirectly to
21 search for books or authors to suggest to the subscriber.

22 Generally, the electronic book suggestion methods may be categorized into two
23 categories, either responsive methods (which respond to a series of subscriber menu
24 entries), or intelligent methods (which analyze data to suggest a book). Using a
25 responsive or intelligent method, the system 200 determines a list of suggested titles or
26 authors and creates a second or third level submenu 856, 857 to suggest the titles for
27 subscriber selection.

28 Responsive methods of suggesting titles include, for example, the use of mood
29 questions, searching for authors, and keyword searching. Using the instruction memory

732 and menu generation hardware (e.g., 607) of the viewer 266, a series of mood questions can be presented on menus to determine a subscribers interest at a particular time. For this methodology, the operations center's 250 processor 404 and instruction memory 416 assign each title mood indicators (and sub-indicators) from a group such as light, serious, violent, short, long, dull, exciting, complex, easy-read, young theme, old theme, adventure, romance, drama, fiction, science-fiction, etc. These indicators are sent to the home system 258 with the text data and are stored in library memory 600. Based upon the subscriber entries, the processor associates a set of indicators with the subscriber's request and a set of books with matching indicators are located for suggesting to the subscriber.

Responsive searches for authors or keywords (a search word provided by the subscriber) are generally performed by the library processor 628 and instruction memory 632 on data stored in the library memory 600. For example, a keyword given by the subscriber may be searched for a match in library memory 600 storing the book reviews, critics and previews databases. Thus, if a subscriber provided an entry of the word "submarine" on an appropriate submenu, the title "Hunt For Red October" may be located by the microprocessor 628 using instruction from a routine in instruction memory 632.

Intelligent methods of suggesting programs include analyzing personal profile data on the subscriber and/or historical data about the subscriber such as past books ordered by the subscriber (or buy data). This method may be performed at the distribution point or operations center 250 by the on-site processor 404 using subscriber databases stored in memory 428. The home system 258 receives the text data including program suggestion information from the distribution point or operations center 250 and generates the program suggestion submenus 855, 856, 857 using the same text data receiving 212 and viewer menu generation hardware (e.g., 607, 621) described above. Software routines and algorithms stored in instruction memories (e.g. 632, 732) are used to analyze historical data and book ordered data to determine a line of books to suggest to the subscriber.

1 The algorithms for this powerful feature of suggesting books or authors to
2 subscribers is disclosed in great detail in U.S. Patent Number 5,798,785, entitled
3 TERMINAL FOR SUGGESTING PROGRAMS OFFERED ON A TELEVISION PROGRAM DELIVERY
4 SYSTEM, filed December 2, 1993, which is incorporated herein by reference.

5 Referring to Figure 13, submenus 858 are shown on the "Books In Your Library"
6 submenu 872 and may be broken into shelf numbers with submenus for each shelf 874,
7 876. The submenus 858 for the "Books You Can Order" submenu 878 is similarly
8 broken out into submenus by shelves 880, 882. These shelves may each be a category or
9 genre of books. Books may be grouped into categories such as best sellers, novels,
10 fiction, romance, etc. See Figure 14d.

11 Referring to Figure 13, the submenu 858 for "Your Current Book" 884 allows a
12 subscriber to select a current book 884 and then determine what page to view. This
13 selection is confirmed with a level two submenu 885. The help submenu 887 provides
14 the subscriber with additional help screens 888. The submenus 858 for available features
15 890 may be broken out into a sequence of separate submenus for each feature 891, 892.

16 Referring to Figure 13, messages can also be sent with the electronic book
17 selection and delivery system 200. A level one message screen provides the subscriber
18 with the ability to select from various messages the subscriber has pending 893. Each
19 message is then shown on a separate submenu screen 894, 895. The message may
20 contain text and graphics.

21 Referring to Figure 13, account information is shown on a level one submenu 896
22 and then follow-on submenus 858 show the recent orders and your account balance 897.
23 There is also a level one submenu for outgoing messages 898 which has a follow-on
24 submenu used as an input screen 899.

25 In addition to the specific features and submenus described in Figure 13 and
26 Figure 14a through Figure 14j, many other variations and features are possible. When
27 a book is finally selected for viewing the title page 886 will appear on the screen followed
28 by a page of text.

III. The Billing And Collection System

In one embodiment, the billing and collection system 278 (shown in Figures 2 and 3) utilizes the latest technology in electronic transaction and telephone switching to track orders, authorize deliveries, bill consumers, and credit publishers automatically. The telephone calls initiated by the phone connector 270 are received by the billing and collection system 278 which responds immediately without human intervention by placing the order and charging the consumers credit card account. Data is compiled periodically and publishers 282 are credited for sales of their books or other text. The billing and collection system 278 may also connect with subscribers through two-way cable connections, cellular, or other communication means. These additional methods are detailed in Section VII.

The billing and collection system 278 communicates with the operations center to track changes in available books and to provide statistical data to the operations center 250.

IV. Public Library, School, and Bookstore System

The electronic book system can be modified to be used at public libraries, schools, bookstores, newsstands, or stand-alone kiosks. Figure 15 shows one possible arrangement of components for the distribution location. The main unit is the file server 900. The file server 900 is a large electronic memory unit that can store thousands of books, newspapers, or periodicals. Various electronic storage means may be used in the file servers, such as hard disks, read-write CD ROMs and read-only CD ROMs.

The system comprises five components; the file server 900, a converter or video connector 904 or connector capable of interfacing to one of the alternative delivery systems presented in Section VII, a controller 908, a viewer 912, and a catalog printer 916. The software for controlling the system is primarily located in the controller 908. The converter or video connector 904 is similar to those described above. In this configuration the controller unit 908 monitors the data being transferred to the file server 900 by the converter 904. The controller 908 may be provided with a viewing screen and several control buttons. When it is necessary to have a larger screen to perform more

1 sophisticated controlling of the system a viewer 266 may be connected to the controller
2 908 and the viewer screen and controls 740 may be used.

3 For security reasons, the controller 908 is only able to download books to public
4 viewers 912 which are authorized to receive books from the particular file server 900.
5 Also for security reasons it is not desirable that the public viewer 912 have access to more
6 than one file server 900. In this way, security can be maintained over the text data for
7 books. The public viewer 912 may be limited to receiving one or two books at a time
8 from the controller 908. When the user of the public viewer 912 needs a new or
9 additional book, the user returns the viewer 912 to the school or public library where the
10 user receives a new book from the controller 908.

11 In order to track the books that are available on the file server 900, the titles of the
12 available books may be printed on a catalog printer 916. The catalog printer 916 is
13 connected to the library controller 908 and the titles of the books are downloaded to the
14 catalog printer 916. For security reasons, the coded text for any of the electronic books
15 may not be authorized for printing using the controller 908 and catalog printer 916. In
16 order to maintain security over the data, none of the electronic book data may be allowed
17 to be downloaded to the printer 916. Once a complete printout of available book titles,
18 magazines, or other textual material is complete, a hard copy of the catalog 920 can be
19 maintained at the file server 900.

20 The system shown may also be used at bookstores. The bookstores can rent the
21 public viewer 912 to customers with the text for one or two books loaded onto the public
22 viewer 912. The public viewer 912 may be provided with an automatic timeout
23 sequence. The timeout sequence would erase the textual data for the books after a certain
24 period of time, for example, two weeks. It is expected that after a period of time (perhaps
25 within two weeks) the renter would return the public viewer 912 to the bookstore and
26 receive additional books for viewing. Using this arrangement, it is also possible for the
27 bookstore to (permanently) sell a viewer 912 to a regular customer. The customer then
28 returns to the bookstore from time to time to receive textual data for a book which the
29 customer can then store permanently on the customer's own viewer 912. Various other

1 configurations are possible for bookstores, schools and public libraries using the file
2 server 900 and public viewer 912 described.

3 V. Use Of A Set Top Converter

4 Existing set top converter boxes such as those made by Scientific Atlanta or
5 General Instruments are presently unequipped to handle the book selection system of the
6 present invention. Although set top converters may be built which include the library
7 functions, hardware modifications are necessary in order to use the book selection system
8 with existing set top converter technology.

9 Figures 16a and 16b are examples of hardware modifications or upgrades. A port
10 is used to attach hardware upgrades described below to a set top terminal. Two upgrades
11 are possible to set top converters 601 to assist in receiving and selecting electronic books,
12 a menu generation card upgrade (Figure 16a) and an information download unit (Figure
13 16b). Each of these upgrades may be connected to the set top terminal unit through an
14 upgrade port. A four wire cable, ribbon cable, FireWire (IEEE 1394B) interface
15 connector, USB connector, or the like may be used to connect the upgrade to the set top
16 converter 601.

17 A card addition 950 to a set top converter 601 is depicted in Figure 16a. The card
18 950 shown provides the additional functionality needed to utilize the book selection
19 system with existing set top converter 601 technology. The card 950 may be configured
20 to slip inside the frame of a set top terminal and become part of the set top terminal, an
21 advanced set top terminal. The primary functions the card 950 adds to the set top
22 converter 601 are the interpreting of data signals, generating of menus, sequencing of
23 menus, and, ultimately, the ability of the subscriber to select a book using either the
24 television or a viewer 266. The card 950 also provides a method for a remote location,
25 such as the cable headend, to receive information on books ordered. The books ordered
26 information and control commands may be passed from the cable headend to the card 950
27 using telephone lines or alternative ordering methods as presented in Section VII.

28 The primary components of the card 950 are a PC chip CPU 952, a VGA graphic
29 controller 954, a video combiner 956, logic circuitry 958, NTSC encoder 960, a receiver

1 962, demodulator (not shown), and a connector 611', which consists of a dialer. The card
2 950 operates by receiving the data text signal from the cable headend through the coaxial
3 cable. The logic circuitry 958 of the card 950 receives data 964, infrared commands 966,
4 and synchronization signals (not shown) from the set top converter 601. Menu selections
5 made by the viewer 266 on the remote control are received by the set top converter's 601
6 IR equipment and passed through to the card 950. The card 950 interprets the IR signal
7 and determines the book (or menu) the subscriber has selected. The card 950 modifies
8 the IR command to send the information to the set top converter 601. The modified IR
9 command contains the channel information needed by the set top converter 601. Using
10 the phone line 968 and dialer 611', the card 950 is able to transmit electronic books
11 ordered information to the cable headend. It is also possible to receive the electronic
12 books over the telephone lines and other telecommunications networks, including
13 wireless networks, and by-pass the video distribution system.

14 These commands are passed through the interface linking the set top terminal's
15 microprocessor with the microprocessor of the hardware upgrades. In this way,
16 subscriber inputs, entered through the set top terminal keypad or remote control, can be
17 transferred to any of the hardware upgrades for processing and responses generated
18 therein can then be sent back to the set top terminal for display. In one embodiment the
19 IR commands 966 are transferred from set top terminal 601 to hardware upgrade.

20 Hardware upgrades may include a microprocessor, interactive software,
21 processing circuitry, bubble memory, and a long-term memory device. In addition to
22 these basic components, the hardware upgrade may make use of an additional telephone
23 modem or CD-ROM device.

24 An information download hardware upgrade 1001 shown in Figure 16b allows the
25 subscriber to download large volumes of information from the operations center 250 or
26 cable headend using a set top terminal 610. The hardware upgrade 1001 will enable
27 subscribers to download data, such as electronic books and electronic magazines, to local
28 storage. Primarily, the hardware upgrade 1001 is an additional local storage unit 1003
29 (e.g., hard disk, floppy, optical disk or magnetic cartridge and may include a

1 microprocessor 1005, instruction memory 1007, and a random access memory 1009, as
2 shown in Figure 16b). A small portable viewer may also provided with the upgrade 1001
3 to enable downloaded text to be read without the use of a television.

4 The downloadable information may be text or graphics supplied by the operations
5 center 250 or cable headend. With the upgrade 1001, electronic books may be
6 downloaded and read anywhere with the viewer 266. Using the upgrade 1001, electronic
7 books may be downloaded and stored in compressed form for later decompression. The
8 electronic books may be decompressed only at the time of viewing. Important text that
9 the public desires immediate access may made available through this system. Text such
10 as the President's speech, a new law, or a recent abortion decision rendered by the
11 Supreme Court may be made immediately available.

12 In one embodiment, electronic book ordering information is stored at each set top
13 terminal 610 until it is polled by the cable headend using a polling request message
14 format. An example of a polling request message format consists of six fields, namely:
15 (1) a leading flag at the beginning of the message, (2) an address field, (3) a subscriber
16 region designation, (4) a set top terminal identifier that includes a polling
17 command/response (or P/F) bit, (5) an information field, and (6) a trailing flag at the end
18 of the message. A similar response frame format for information communicated by the
19 set top terminal to the cable headend in response to the polling request may be used.

20 Figure 17 shows components of a set top terminal 610'. The components include
21 a data receiver 617' and a data transmitter 1011. The data transmitter provides upstream
22 data communications capability between the set top terminal 610' and the cable headend.
23 Upstream data transmissions are accomplished using the polling system described and,
24 using a data transmitter 1011. Both receiver 617' and transmitter 1011 may be built into
25 the set top terminal 610' itself or added through an upgrade module. Regardless of the
26 specific hardware configuration, the set top terminal's data transmission capabilities may
27 be accomplished using the hardware shown in Figure 17.

28 Figure 17 shows RF signals, depicted as being received by a data receiver 617'
29 and tuner 613 working in unison. Both of these devices are interfaced with the

1 microprocessor 1013, which receives inputs 1015, from the subscriber, either through a
2 set top terminal's keypad, a remote control unit or viewer 266. Generally, all cable
3 signals intended for reception on the subscriber's TV are accessed by the tuner 613 and
4 subsequently processed by the processing circuitry 1017. This processing circuitry 1017
5 typically includes additional components (not shown) for descrambling, demodulation,
6 volume control and remodulation on a Channel 3 or 4 TV carrier.

7 Data targeted to individual set top terminals is received by the data receiver 617'
8 according to each set top terminal's specific address or ID. In this way, each addressable
9 set top terminal 610' only receives its own data. The data receiver 617' may receive set
10 top terminal 610' specific data in the information field of the signal frame described or
11 on a separate data carrier located at a convenient frequency in the incoming spectrum.

12 The received data includes information regarding electronic books and menus
13 available for selection. The subscriber may enter a series of commands 1015 using a
14 keypad or remote control in order to choose an electronic book or menu. Upon receipt
15 of such commands, the set top terminal's microprocessor 1013 instructs the tuner to tune
16 to the proper frequency of the channel carrying data and subsequently instructs the
17 processing circuitry 1017 to begin descrambling of this data.

18 Upon selection of an electronic book, the microprocessor 1013 stores any
19 selection information in local memory (not shown) for later data transmission back to the
20 cable headend. The set top terminal's microprocessor 1013 coordinates all CATV signal
21 reception and also interacts with various upstream data transmission components.
22 Typically, the data transmitter 1011 operates in the return frequency band between 5 and
23 30 MHZ. In an alternative embodiment, the frequency band of 10 to 15 MHZ may be
24 used. Regardless, however, of the frequency band used, the data transmitter 1011 sends
25 information to the cable headend in the information field of the response frame described.
26 Those skilled in the art will recognize that a number of variations and combinations of
27 the above-described set top terminal hardware components may be used to accomplish
28 upstream data transmissions.

VI. Books-On-Demand System

The electronic book system 200 described may also be configured in a book-on-demand style. Figure 18a shows one example of a configuration for a book-on-demand system. A book on demand system requires more powerful two-way communications between the consumer's home, bookstore, school or public library and either the operations center 250 or a distribution site 1020 such as the cable headend. In one embodiment, this type of two-way communication can be provided by the hardware shown in Figure 17 and described above. Additional methods related to alternative communication paths are presented in Section VII.

Referring to Figure 18a, in a book-on-demand system, the subscriber selects the book to be download from an available menu of books (see for example Figures 14d and 14e). The data for menus of available books is usually sent to the subscriber location by the distribution site 1020. After the subscriber's menu selection, information about the subscriber selection (or request) is then communicated to either a distribution point 1020 (such as a cable headend) or the operations center 250. Upon receipt of this request, the needed textual and graphical information for the book is spooled and sent to the subscriber. In this manner, electronic books are only sent when requested by the subscriber and are sent immediately upon demand for the electronic book (or text).

In order to support such a demand system, the text delivery and distribution must be conducted on a strong nodal architecture distribution system, such as, a video-on-demand cable or telephone television system, through use of individual telephone calls on the public telephone system or cellular phone system, through the use of the Internet, or a number of other data network options.

The book-on-demand system allows for a greater selection of electronic books to the subscriber and limits the amount of communicated book data that is unnecessary or unneeded. It also provides the electronic book to the subscriber in a much timelier fashion.

In addition to a stronger distribution system, a book-on-demand system requires a distribution point 1020 to have more sophisticated equipment to access and "spool out"

1 the textual information. This can be accomplished using file server technology 1024 for
2 storing the books and distribution technology such as ATM 1028 or telephone-type
3 switching (not shown) to distribute the textual information. The file server 1024 and
4 distribution technology that can be used in configuring such a book-on-demand system
5 is described in U.S. Patent No. 5,262,875 and U.S. Patent 5,218,695, cited above.

6 Figure 18a shows an embodiment for a book-on-demand system that utilizes file
7 server technology. In addition to books, the embodiment of Figure 18a will support
8 distribution of nearly any digital data. Books or textual files are received from publishers
9 282 and other sources through local feeds 1032, ATM 1028, or by satellite dish 1036, for
10 example. The data is then stored in memory 1040 at the file server 1024. In one
11 embodiment, the distribution point 1020 is a cable headend that receives requests from
12 subscribers and delivers text to subscribers over a two-way communication system (such
13 as a video-on-demand system (VOD) 1044).

14 The library 262 can be connected to either a basic premium-type service cable
15 system 1048, a near video-on-demand type cable system (or pay-per-view (PPV) 1052)
16 or a video-on-demand cable system 1044. In connecting with either of these three
17 systems the library 262 may access the cable directly or may access the system through
18 a set top terminal 601', 601'', or 601'''.
19

20 Using the two-way video-on-demand system 1044, a subscriber is able to request
21 a specific book title and receive that text immediately following its request. To
22 accomplish this, the distribution point 1020 transmits a list of available books through
23 the cable delivery system to the library 262. The library 262 displays the list of available
24 books on a menu or similar format. As described earlier, the library 262 may use menus
25 which list categories of available books to form its request from the distribution point
26 1020. After selecting a book the library 262 then sends a request signal on the two-way
27 communication system 1044 back to the distribution point 1020. This request signal can
28 be handled in two ways. The library 262 either initiates the request or the distribution
point 1020 polls the various libraries on to the two-way system 1044. Upon receiving the

1 request for the book title, the text associated with that book title is transmitted to the
2 library 262 using the two-way cable system 1044.

3 Figure 18b is an expanded view of an operations center 250 that supports a
4 regional or national book-on-demand system. In fact, the operations center 250 shown
5 supports distribution of nearly any digital data. The operations center 250 supports
6 multiple feeds to receive digital information by tape 1060, 1060', ATM 1028, or satellite
7 1036. The information is processed through an input MUX 1064 and a small file server
8 1068 before reaching the master file server 1072. Digital data such as books received
9 from publishers 282 is then stored on the master file server 1072. The digital data may
10 be stored compressed in a standard format such as MPEG2.

11 A system controller 1076 provides control over the regional or national book-on-
12 demand system. Books may be packaged into groups to provide feeds to various cable
13 headends. In addition, scheduling and marketing research are conducted at the operations
14 center 250. In order to handle the scheduling and market research, book buy data is
15 received at the operations center 250 through a multiplexer 1082. Book buy information
16 can be provided by the operation center 250 to the billing and collection system 278.

17 The operations center 250 is also equipped to insert messages or advertisements
18 into the file server. These messages or advertisements will eventually be received by the
19 subscribers.

20 The master file server 1072 uses an output multiplexer 1080 and ATM 1028 as
21 well as satellite connections to distribute digital data. In one embodiment, cable
22 headends receive text data on books from the master file server 1080 through the output
23 multiplexer 1028 and an ATM system 1028. After receiving the digital book data, the
24 cable headends store the books in a local file server 1024. Figure 18a's distribution point
25 1020 is an example of a cable headend which may receive data from the operations center
26 250 of Figure 18b through an ATM hookup 1088 or satellite hookup.

27 VII. Alternative Delivery And Ordering Methods

28 Electronic books and related data, including electronic book menu data, may be
29 provided to subscribers by use of an on-demand delivery system in which electronic

1 books are delivered after an order is received by the delivery system. The delivery system
2 may supply the electronic books in real time or near-real time (i.e., near on-demand), or
3 after a delay period that allows the delivery system to process, package and transmit the
4 electronic book. Alternatively, the delivery system may broadcast one or more electronic
5 books in a continuous fashion. In this alternative, the subscriber indicates a desired
6 electronic book from a list of the broadcast electronic books. The delivery system may
7 include a billing system that debits a subscriber's account, or debits a credit card, for
8 example, upon delivery of the electronic book. The delivery system, or a related
9 authorization system, may provide a local authorization code that allows the subscriber
10 to decrypt, store and view the desired electronic book.

11 a. Use of TV Program Broadcast Delivery System for Electronic Book
12 Delivery

13 i. Delivery System Description

14 In addition to advances in television broadcast technology, government regulatory
15 agencies have placed requirements on the broadcast television industry. In particular, the
16 over-the-air broadcast television networks will soon transition to high definition
17 television (HDTV) - a digital broadcast television standard. These broadcasters may elect
18 to provide a single HDTV digital signal in their allotted bandwidth, with the remaining
19 bandwidth used for standard definition television (SDTV) digital programming.
20 Alternatively, broadcasters may elect to make use of their bandwidth for data-related
21 services, such as the delivery of electronic books.

22 This embodiment relates to an electronic book delivery system using a digital
23 television program delivery system. This embodiment may be used in at least two
24 domains: delivery of electronic books embedded in the broadcast digital multiplex signal
25 using terrestrial, over-the-air media; and delivery of electronic books embedded in the
26 broadcast digital multimedia signal over an existing cable television system. Over-the-air
27 delivery includes standard terrestrial television broadcasts. Cable delivery systems
28 include coaxial cable systems, fiber optic delivery systems, and telephone delivery
29 systems (including T1 and T3 lines, Integrated Services Digital Network (ISDN) lines

1 and Asymmetric Digital Subscriber Lines (ADSL)). In addition, electronic books may
2 be delivered within the broadcaster's signal by direct satellite broadcast, by wireless
3 broadcasts, and by other wired means including local area networks.

4 Figure 19 shows a broadcast television environment 1100 in which a broadcast
5 program provider, such as a national broadcaster 1110, provides digital multiplex
6 television programming with embedded electronic book data 1111 to a broadcast affiliate
7 1112. The programming with embedded electronic book data 1111 may be provided to
8 the broadcast affiliate 1112 by any suitable means. For example, the national broadcaster
9 1110 may provide the programming with embedded electronic book data 1111 by satellite
10 transmission using a satellite broadcast system 1120. The satellite broadcast system 1120
11 may include an uplink site 1121, a satellite 1122, and a downlink site 1123. The satellite
12 broadcast system 1120 may transmit the programming with embedded electronic book
13 data 1111 to the broadcast affiliate 1112 and directly to home systems 258', 258'', and
14 258''' at remote locations such as subscribers' homes, for example.

15 The broadcast affiliate 1112 may provide digital multiplex television
16 programming with embedded electronic book data 1115 to intermediate locations such
17 as local cable system 1114. Alternately, the broadcast affiliates 1112 may provide the
18 programming with embedded electronic book data 1115 directly to the subscriber's home
19 systems 258', 258'', and 258'''. The local cable system 1114 that receives the
20 programming with embedded electronic book data 1115 may in turn provide the
21 programming with embedded electronic book data 1115 to the home systems 258', 258'',
22 and 258'''.

23 The home systems 258', 258'', and 258''' may receive digital television signals
24 from any device capable of receiving digital TV signals, including digital televisions,
25 digital set top boxes and personal computers, or any combination of these devices, or
26 home subsystems may have a built-in digital TV receiver. The home systems 258' 258'',
27 and 258''' may receive the programming with embedded electronic book data 1115 by
28 cable, including coaxial cable and fiber optic cable, by telephone cable (including T1 and
29 T3 lines, Integrated Services Digital Network (ISDN) lines and Asymmetric Digital

Subscriber Lines (ADSL)). Alternately, the home systems 258', 258", and 258''' may receive the programming with embedded electronic book data 1111 directly from the national broadcaster 1110 using the satellite broadcast system 1120. For example, the home system 258''' receives direct broadcast satellite programming with embedded electronic book data using a backyard satellite antenna 1143.

Also coupled to the home systems 258', 258", and 258''' may be an Internet 1105. The Internet 1105 provides access to web sites such as the web site 279. The Internet 1105 may also connect to the billing and collection system 278, or operations center 250, which is responsible for formatting and delivering the electronic book data to the broadcast affiliate 1112 and the national broadcaster 1110 to be embedded into their respective program signals for delivery. The operations center 250 may use the Internet 1105 to post electronic book ordering menus, such as provided in the menu system 851 shown in Figure 13. The billing and collection system 278 may use the Internet 1105 to receive orders and payment for the purchases of electronic books. The electronic book ordering menu 851 may be provided as part of the broadcast from the national broadcaster 1110, the broadcast affiliate 1112, or the local cable system 1114. Alternatively, the electronic book ordering menu 851 may be downloaded from an Internet web site or alternately viewed directly on the Internet web site. The use of the Internet 1105 for these purposes will be described later in more detail.

In Figure 19, the national broadcaster 1110 may be a television program broadcaster. Alternately, the national broadcaster 1110 may be a radio program broadcaster, or a combined television and radio broadcaster. The national broadcaster 1110 may also broadcast any other type of data or communication, either separately or in combination. Likewise, the broadcast affiliate 1112 may broadcast television or audio or both and may also broadcast any other data or communication, either separately or in combination. The national broadcaster 1110 and the broadcast affiliate 1112 may broadcast analog signals and any type of digital signals including packet data. Digital data broadcast by the national broadcaster 1110 and the broadcast affiliate 1112 may include high definition television and standard definition television signals.

1 Figure 20 is a flowchart of steps involved in processing text from the publisher
2 or provider 282 that may occur at the operations center 250. As shown in step S500, the
3 publisher 282 processes data files of text for books, and compresses, encrypts and sends
4 the data files to the operations center 250. Text files for books may be sent one book at
5 a time. As shown in step S504, the operations center 250 receives and processes the data
6 stream from the publisher 282. Part of this processing may include encryption and error
7 correction and storage for future delivery purposes. Text files may be delivered for
8 receipt by multiple home systems simultaneously, or to a specific individual home
9 system.

10 In one embodiment, as shown in step S509, files are broken into smaller packets
11 of information. Header information is added to the packets. The bit stream is converted
12 from a serial digital bit stream to a digital stream that is compatible for insertion into the
13 broadcaster's video/audio program multiplex signal. Step S513 shows the multiplexing
14 of digital data into the appropriate data fields within the video/audio program multiplex.
15 The digital data may be treated as an ancillary MPEG2 service, being placed into the
16 multiplex as private data, carried either in the adaptation header of the MPEG2 transport
17 packets or in a separate transport stream altogether. Step S513 also shows the operations
18 center 250 performing the necessary modification to the industry standard MPEG
19 Program Map Table and Program Specific Information.

20 ii. In-Home Reception Options for a Broadcast Delivery System

21 Figures 21a-21g show reception options at the remote locations such as at a
22 subscriber's home. In Figure 21a, the home system 258 is coupled to a digital set top
23 terminal 1220. The set top terminal 1220 receives the programming with embedded
24 electronic book data 1115 from the broadcast affiliate 1112 or the local cable system
25 1114. Alternately, the national broadcaster 1110 may provide the programming with
26 embedded electronic book data by use of the satellite broadcast system 1120. In this
27 alternative, the set top terminal 1220 would be coupled to a local, or backyard, satellite
28 dish antenna or similar device. In yet another alternative, the set top terminal 1220

1 receives programming from both the satellite broadcast system 1120, the local cable
2 system 1114, and directly from the broadcast affiliate 1112 using terrestrial broadcast.

3 Also shown in Figure 21a is a telephone 1178 that may be used to communicate
4 with the billing and collection system 278, and a personal computer (PC) 1172 and a
5 modem 1173 that may be used to communicate with the Internet 1105. The personal
6 computer 1172 may be coupled to the set top terminal 1220 using signal path 1174. The
7 signal path 1174 may include a cable connection such as a RS-232 cable, USB format
8 interface, Firewire interface, and connectors or by wireless means, such as infrared
9 signaling and radio frequency signaling, for example.

10 The set top terminal 1220 performs the necessary processing to send the
11 programming with embedded electronic book data 1115 to the home system 258. The
12 set top terminal 1220 may demultiplex the programming with embedded electronic book
13 data 1115 and supply the demultiplexed signal to the home system 258. To do this, the
14 set top terminal 1220 extracts the data related to the electronic book from the digital
15 program multiplex signal.

16 The set top terminal 1220 may receive commands from a remote control 1900.
17 The set top terminal 1220 may include communication devices 1221 that allow reception
18 and transfer of data with external sources such as the Internet 1105. For example, the set
19 top terminal 1220 may include a telephone modem, a cable modem, a wireless modem,
20 a fiber optic connector, a LAN connector, or any combination of these devices. Using
21 this connection to the Internet 1105, the set top terminal 1220 and PC 1172 may access
22 the billing and collection system 278 or alternatively connect to the Internet 1105 to
23 access the Internet web site 279 to view electronic book ordering menus 851 provided by
24 the operations center 250.

25 The set top terminal 1220 has input and output ports for communication with
26 other local and remote devices. Although the local cable system 1114 or terrestrial
27 broadcast methods are the most prevalent transmission mediums for delivering
28 programming with embedded electronic book data to the home, telephone lines
29 (including T1 and T3 lines, Integrated Services Digital Network (ISDN) lines and

Asymmetric Digital Subscriber Lines (ADSL)), cellular networks, fiber optics, local area networks, Personal Communication Networks, and analog and digital satellites and similar technology for transmitting to the home can be used interchangeably. The set top terminal 1220 may have output ports that provide communications from the set top terminal 1220 to the home system 258 and a television. Also, the set top terminal 1220 may contain a phone jack that can be used for maintenance, trouble shooting, reprogramming and additional customer features. The phone jack may also be used to connect the set top terminal 1220 with the Internet 1105 for the purpose of ordering electronic books. Alternately, the set top terminal may support other communication interfaces using the appropriate interface device connector. The electronic book data embedded within the programming 1115 contains data, such as the electronic book ordering menu 851 information, to advise the subscriber which electronic books are available for purchase. Once the electronic book ordering menus 851 have been received by the home system 258, the home system 258 can generate the appropriate menus. Alternately, menu retrieval or viewing and electronic book selecting and ordering may be achieved using the Internet web site 279 on the Internet 1105, which is accessed using the provided modem interface.

Figure 21b shows an alternate arrangement of components for receiving the broadcast digital programming with embedded electronic book data 1115 and providing it to a home system 258. In Figure 21b, the digital television 1171 is coupled to the broadcast affiliate 1112 to receive the programming 1115. The digital television 1171 may also receive the programming with embedded electronic book data 1115 from the local cable system 1114 or from the satellite broadcast system 1120.

The digital television 1171 may include an optional smart card 1180 that performs the functions described above for the set top terminal 1220. For example, the smart card 1180 may include a cable modem, a telephone modem, a wireless modem, a fiber optic connector, or a LAN connector. Also shown in Figure 21b is the personal computer 1172 and the modem 1173, which function as before to connect to the Internet 1105. The functions of the digital television 1171 may be controlled by the remote control 1900,

1 using either infrared signals or radio frequency signals, for example. Using this
2 connection to the Internet 1105, the television 1171 and PC 1172 may access the billing
3 and collection system 278 or alternatively connect to the Internet 1105 to access the web
4 site 279 to view electronic book ordering menus 851 provided by the operation center
5 250.

6 Figure 21c shows another arrangement of components for receiving the broadcast
7 digital programming with embedded electronic book data 1115. In Figure 21c, a digital
8 television 1171' incorporating the smart card 1180 receives the programming with
9 embedded electronic book data 1115 from the local cable system 1114 and performs all
10 the functions of the library 262 described previously, including connecting to the viewer
11 266. The television 1171' could also receive the programming with embedded electronic
12 book data 1115 using other media including direct satellite broadcast, fiber optic
13 connections, local area networks, such as an ethernet, the Plain Old Telephone Service
14 (POTS), other telephone delivery systems (including T1 and T3 lines, Integrated Services
15 Digital Network (ISDN) lines and Asymmetric Digital Subscriber Lines (ADSL)) and by
16 over-the-air broadcast from the broadcast affiliate 1112. The television 1171',
17 incorporating the smart card 1180, includes some or all of the functionality of the
18 personal computer 1172 shown in Figure 21b, for example. The television 1171'
19 connects to the Internet 1105 and is able to access the web site 279 to view electronic
20 book ordering menus 851 provided by the operations center 250. The remote control
21 1900 may be used to control the television 1171' and library 262. The television 1171'
22 may also, in its programming, include a soft key board 1174 that is displayed on the
23 display of the television 1171'. The remote control 1900 can then be used to operate
24 "soft keys" on the soft key board 1174. The television 1171' may also incorporate a
25 separate key board 1174' that is used to control the television 1171' and the library 262
26 and to operate the television 1171' in its personal computer role. The key board 1174'
27 may be connected to the television 1171' by a wired connection. Alternately, the key
28 board 1174' may communicate with the television 1171' and library 262 by wireless
29 means including infrared signaling, radio frequency signaling and by other optical means

1 including a laser. The television 1171' and library 262 may connect to a telephone
2 system using signal path 1154.

3 Figure 21d shows yet another arrangement of components for receiving the
4 broadcast digital programming with embedded electronic book data 1115. In Figure 21d,
5 a digital television 1171' incorporating a smart card that functions as a complete
6 electronic book home system 258 receives the programming with embedded electronic
7 book data 1115 from the local cable system 1114 and performs all the functions of the
8 home system 258 described previously, and displays the electronic book data on the
9 television display. The television 1171' could also receive the programming with
10 embedded electronic book data 1115 using other media including direct satellite
11 broadcast, fiber optic connections, local area network, such as an ethernet, the POTS,
12 other telephone delivery systems (including T1 and T3 lines, Integrated Services Digital
13 Network (ISDN) lines and Asymmetric Digital Subscriber Lines (ADSL)) and by over-
14 the-air broadcast from the broadcast affiliate 1112. The television 1171', incorporating
15 the home system 258 functionality, may include some or all of the functionality of the
16 personal computer 1172 shown in Figure 21b, for example. The television 1171'
17 connects to the Internet 1105 and is able to access the web site 279 to view electronic
18 book ordering menus 851 provided by the operations center 250. The remote control
19 1900 may be used to control the television 1171' and home system 258. The television
20 1171' may also, in its programming, include a soft keyboard 1174 that is displayed on the
21 display of the television 1171'. The remote control 1900 can then be used to operate
22 "soft keys" on the soft keyboard 1174. The television 1171' may also incorporate a
23 separate keyboard 1174' that is used to control the television 1171' and home system 258
24 and to operate the television 1171' in its personal computer role. The keyboard 1174'
25 may be connected to the television 1171' by a wired connection. Alternately, the
26 keyboard 1174' may communicate with the television 1171' and home system 258 by
27 wireless means including infrared signaling, radio frequency signaling and by other
28 optical means including a laser. The television 1171' and home system 258 may connect
29 to a telephone system using signal path 1154.

1 Figure 21e shows another arrangement of components for receiving the broadcast
2 digital programming with embedded electronic book data 1115. In Figure 21e, a PC 1172
3 with digital TV receiver incorporating the smart card 1180 receives the programming
4 with embedded electronic book data 1115 from the local cable system 1114 and performs
5 all the functions of the library 262 described previously, including connecting to a viewer
6 266. The PC 1172 could also receive the programming with embedded electronic book
7 data 1115 using other media including direct satellite broadcast, fiber optic connections,
8 local area network, such as an ethernet, the POTS, other telephone delivery systems
9 (including T1 and T3 lines, Integrated Services Digital Network (ISDN) lines and
10 Asymmetric Digital Subscriber Lines (ADSL)) and by over-the-air broadcast from the
11 broadcast affiliate 1112. The PC 1172 connects to the Internet 1105 and is able to access
12 the web site 279 to view electronic book ordering menus 851 provided by the operations
13 center 250.

14 Figure 21f shows another arrangement of components for receiving the broadcast
15 digital programming with embedded electronic book data 1115. In Figure 21f, the PC
16 1172 with digital TV receiver incorporating a smart card that functions as a complete
17 electronic book home system 258 receives the programming with embedded electronic
18 book data 1115 from the local cable system 1114 and performs all the functions of the
19 home system 258 described previously. The PC 1172 could also receive the
20 programming with embedded electronic book data 1115 using other media including
21 direct satellite broadcast, fiber optic connections, local area network, such as an ethernet,
22 the POTS, other telephone delivery systems (including T1 and T3 lines, Integrated
23 Services Digital Network (ISDN) lines and Asymmetric Digital Subscriber Lines
24 (ADSL)) and by over-the-air broadcast from the broadcast affiliate 1112. The PC 1172
25 connects to the Internet 1105 and is able to access the web site 279 to view electronic
26 book ordering menus 851 provided by the operations center 250.

27 Figure 21g shows another arrangement of components for receiving the broadcast
28 digital programming with embedded electronic book data 1115. In Figure 21g, the home
29 system 258 contains a digital TV receiver 1613 to receive the programming with

1 embedded electronic book data 1115 from the local cable system 1114. The home system
2 258 connects to the Internet 1105 and is able to access the web site 279 to view electronic
3 book ordering menus 851 provided by the operations center 250.

4 Figure 22 presents the hardware configuration of a home system 258 to support
5 delivery of electronic books using the TV program broadcast delivery system. The home
6 system 258 in Figure 22 includes a home system front end 259 and home system backend
7 259'. The home system front end 259 can vary based on the delivery system from which
8 electronic book data is being received. The home system backend 259' and its associated
9 components and functionality are consistent regardless of the delivery system used and
10 are as described in Section II above. The home system front end 259 performs several
11 functions, such as receiving digital data directly, or receiving TV program broadcast
12 signals, and stripping (or extracting) the data from the signal. Various hardware
13 configurations may be utilized to achieve the desired functions of the home system front
14 end 259. For example, as shown in Figure 22, the home system 258 can be configured
15 to receive digital program multiplexes from the set top terminal 1220, from the TV 1171,
16 or from the computer 1172 using the connector 1617. Alternatively, the home system
17 258 can receive the RF channel in which the digital program multiplex signal is contained
18 using the digital TV receiver 1613 and provide the signal to a digital program broadcast
19 connector 1617 to extract the electronic book data from the signal. Finally, the home
20 system 258 can receive a digital data stream, which has already been extracted from the
21 digital program multiplex, using a connector 1619. Once the digital data that is related
22 to the electronic book system has been extracted from the TV program broadcast signal,
23 the digital data is provided to the digital logic 609 in the home system 258 for continued
24 processing, as described in Section II.

25 To receive and strip the data from the digital TV program signal at the consumer's
26 home, the connector 1617 is used. Figure 23 is a flowchart of processes performed by
27 the connector 1617. The connector 1617 receives the digital program multiplex signal
28 in step S1607, removes the MPEG control information from the signal in step S1608,
29 determines if the stream contains any electronic book data embedded within it in step

1 S1612, extracts the electronic book data from the signal in step S1616, and communicates
2 the extracted electronic book data stream to digital logic components 609 in step S1620.

3 iii. Electronic Book Ordering Process for TV Program Broadcast
4 Delivery

5 As described in Section II above, a subscriber selects their desired electronic book
6 from a menu system. This menu system and its contents are updated by the operations
7 center 250 using information delivered to the home system 258 either periodically
8 distributed over the TV program broadcast delivery system, or delivered to the home
9 system 258 by the billing and collection system 278 upon ordering a new electronic book.
10 Order requests for electronic books made from this menu are forwarded to the billing and
11 collection system 278 for processing.

12 In the case where the delivery is done using a two-way cable system, the set top
13 terminal 1220 can be used to convey order request information to the local cable system
14 1114. The local cable system 1114 will in turn be in communication with the billing and
15 collection system 278 or the operations center 250 that handle requests from the set top
16 terminal 1220 for electronic book ordering or billing purposes. Further, telephone lines
17 with modems may be used to transfer information from the set top terminal 1220 to the
18 billing and collection system 278 or the operations center 250. Alternately, the set top
19 terminal 1220 may incorporate a cable modem, a wireless modem, LAN connectors, T1
20 and T3 connectors, Asymmetric Digital Subscriber Line (ADSL) Connectors, Integrated
21 Digital Service Network (ISDN) connectors or other advanced communications interfaces
22 for transmitting information to the cable system 1114 or over alternate communication
23 paths directly to the billing and collection system 278 or the operations center 250.
24 Alternatively, the home system 258 may contact the billing and collection system 278
25 directly over any of these communication paths.

26 Figures 24a-24c show alternate arrangements of an ordering process that can be
27 used with the programming with embedded electronic book data 1111 or 1115. In the
28 discussion that follows, the subscriber receives the programming with embedded
29 electronic book data 1115 from the local cable system 1114. However, the order process

1 may also be used when the programming with embedded electronic book data 1115 is
2 provided by the broadcast affiliate 1112 or the satellite broadcast system 1120, or from
3 any other entity capable of providing digital broadcast programming with embedded
4 electronic book data.

5 In Figures 24a-24c, electronic book order requests may be provided over a variety
6 of telecommunications media including using a cable modem to the billing and collection
7 system 278; over a proprietary two-way transmission system to the billing and collection
8 system 278; over a fiber optic cable system to the billing and collection system 278; using
9 a telephone modem to the billing and collection system 278, using existing telephone
10 lines; using a cellular modem over wireless telecommunication systems; using T1 and T3
11 lines, Asymmetric Digital Subscriber Lines, Integrated Digital Services Network lines,
12 and using a telephone and the POTS. Alternately, the electronic book order requests may
13 also be provided over a LAN, such as an ethernet.

14 In Figure 24a, the national broadcaster 1110 provides the programming with
15 embedded electronic book data 1111 to the broadcast affiliate 1112. The broadcast
16 affiliate 1112 sends the programming with embedded electronic book data 1115 to the
17 local cable system 1114. The local cable system 1114 sends the programming with
18 embedded electronic book data 1115 to the home system 258. To receive the requested
19 electronic book from the programming with embedded electronic book data at the home
20 system 258, the subscriber may initiate an order request. In the embodiment shown in
21 Figure 24a, the subscriber sends an order request 1190 to the billing and collection
22 system 278, which then initiates the delivery of the requested electronic book data from
23 the operations center 250 for inclusion in the programming.

24 Electronic books may also be received at the home system 258 without the
25 subscriber providing the order request. Another subscriber may provide an electronic
26 book for delivery to the home system 258 as a gift, for example. Electronic books also
27 may be sent to the home system 258 on a trial, or approval basis. For example, a trial
28 electronic book may be sent to a home system 258 on a trial basis and the trial electronic
29 book could include a code that prevents viewing after a set, elapsed time from receipt at

1 the home system 258. To retain viewing privileges for the trial electronic book, the
2 subscriber could indicate a desire to purchase the trial electronic book. The operations
3 center 250 would then return an authorization code that permits the subscriber to retain
4 the trial electronic book on a permanent basis. Alternatively, the delivery system 200
5 could provide a portion of an electronic book, in an unencrypted format, such as the first
6 chapter, and the subscriber would have to purchase the electronic book to receive the
7 authorization code to decrypt the remainder of the electronic book.

8 Figure 24b shows an alternate arrangement of the ordering process. The ordering
9 process shown in Figure 24b differs from that shown in Figure 24a in that an order
10 request 1190' is sent to the billing and collection system 278, which then initiates
11 delivery of the electronic book data for insertion by the broadcast affiliate 1112.

12 Figure 24c shows yet another arrangement of the ordering process. In Figure 24c,
13 an order request 1190" is sent to the billing and collection system 278, which then
14 initiates delivery of the electronic book data for insertion by the national broadcaster
15 1110.

16 b. Operation of the Ordering System Using the Internet

17 In the one-way delivery environment typified by the TV program broadcast
18 delivery environment, the use of the Internet can provide ubiquitous access to subscribers
19 for ordering electronic books. The subscriber may log on to the Internet web site 279,
20 using the PC 1172 of Figures 21a, 21b, 21e, or 21f, or the television 1171' of Figures 21c
21 or 21d, or the home system 258 of Figure 21g. The subscriber may then enter a
22 subscriber identification. The Internet web site 279 may then present an individualized
23 menu to the subscriber. The subscribers may view the individualized menu on the PC
24 1172, television 1171' or home system 258, for example. The individualized menu may
25 be based on subscriber specific data, such as past electronic books ordered, for example.

26 When the electronic book ordering is performed on the Internet web site 279, the
27 Internet web site 279 may also recognize the subscriber 285, based on the subscriber's
28 automatic number identification (ANI), user name, user identification, and Internet
29 address (i.e., REMOTE_HOST, REMOTE_ADDR, and HTTP_NAME), for example.

1 The subscriber may also be identified by a unique subscriber identifier that is provided
2 to the subscriber upon subscribing to a broadcast television service. Other means for
3 identifying a subscriber include special features such as browser cookies. A browser
4 cookie is a mechanism that allows a web site server to store limited amounts of
5 information on a browser. The information is typically information sent to a subscriber's
6 terminal using a Set-cookie HTTP response field header. The Set-cookie field contains
7 the cookie content as a name/value pair, and can also contain information explaining
8 when the cookie will no longer be valid (expires), the Internet domain for which the
9 cookie is valid (domain), and the path portion of the URL within this domain for which
10 the cookie is valid. Browsers that understand cookies will store the data on the set top
11 terminal's hard disk, for example, and will return these data to the web site server from
12 which the cookie originated within a cookie request header field. Cookies are useful for
13 storing state information (when the subscriber last visited the web site, which resources
14 the subscriber last used, for example) on the browser, in such a way that the information
15 is not lost when the subscriber leaves the web site or shuts down the browser.

16 A web site, such as the web site 279, may use cookies to customize electronic
17 book ordering for the subscriber. For example, the web site 279 may welcome a
18 subscriber to the web site 279, based on the information in the cookie, and may navigate
19 the subscriber to a menu, or individualized menu, based on previous orders provided by
20 the subscriber. When the subscriber is identified, the web site 279 may create the
21 individualized order menu, which the specific subscriber may download to the home
22 system 258.

23 Once an order for an electronic book has been made, the billing and collection
24 system 278 processes the order and initiates a request to the operations center 250 for the
25 delivery of the requested electronic book for delivery over the TV program broadcast
26 delivery system.

27 Figure 25 is a flow chart of the major steps associated with ordering an electronic
28 book using the Internet. The flow chart assumes the broadcast environment of Figure 19.

1 The process begins with step S100. In step S110, the PC 1172 of Figures 21a,
2 21b, 21e, or 21f, or the television 1171' of Figures 21c or 21d, or the home system 258
3 accesses the web site 279. The web site 279 may be accessed by entering the address of
4 the web site 279 into a location window of a web browser, by activating a hypertext link
5 provided on the home system 258 menu or within an actual electronic book being viewed
6 in the viewer 266, or by activating a hypertext link received from a different web site.
7 The process then moves to step S120.

8 In step S120, a data signal showing the web site 279 home page is transmitted to
9 the set top terminal 220, and the web site 279 home page is displayed on the requesting
10 device. The process then moves to step S130. In step S130, the web site 279 receives
11 the order signal 1190 for an electronic book selected by a subscriber. The order signal
12 1190 includes an electronic book identifier and the address and identification of the
13 requesting home system 258. The process then moves to step S140.

14 In step S140, the web site 279 transmits the authorization request 1196 to the
15 billing and collection system 278. The process then moves to step S150. In step S150,
16 the billing and collection system 278 determines if the home system 258 from which the
17 order signal 1190 originated is authorized to receive the selected electronic book. The
18 billing and collection system 278 may evaluate the past credit history of the requesting
19 subscriber. The billing and collection system 278 may determine if the subscriber's
20 account is delinquent. If the home system 258 is not authorized to receive the selected
21 electronic book, the process moves to step S160. Otherwise, the process moves to step
22 S170.

23 In step S160, the billing and collection system 278 sends a message to the
24 requesting home system 258 stating that the selected program cannot be accessed, along
25 with the reason for no access. The process then moves to step S190 and ends.

26 In step S170, the billing and collection system 278 sends an authorization signal
27 1191 to the operations center 250. The process then moves to step S180. In step S180,
28 the operations center 250 retrieves and embeds the requested electronic book data within
29 the programming. The process then moves to step S190 and ends.

1 The method of ordering electronic books using the Internet is not limited to the
2 TV program broadcast delivery embodiment. This ordering method is general in nature
3 and may be used for ordering electronic books to be delivered using any of the delivery
4 methods presented herein.

5 c. Internet Delivery Methods

6 Figure 26 is an alternate delivery plan 301' that provides for electronic book
7 delivery using the Internet. In Figure 26, the publishers 282 provide the electronic books
8 to be posted at the Internet web site 279. The publishers may convert the text and
9 graphical data to digital format, compress the digital data, and upload the compressed
10 digital data to the Internet web site 279. Alternately, the publishers 282 may arrange for
11 an outside conversion activity 283 to convert the text and graphical data to digital format.
12 The conversion activity 283 may then provide the digital data to the Internet web site 279.
13 For example, a large on-line bookstore could gather publications in electronic form from
14 a variety of publishers, or could convert hard-copy books to electronic form, and post the
15 electronic books on the Internet such as at the Internet web site 279.

16 The electronic books may then be transferred using a public switched telephone
17 network (PSTN), for example, or other communications systems, direct to a subscriber
18 285, a library 286 and a bookstore 287. The library 286 and the bookstore 287 may also
19 provide electronic books to the subscriber 285.

20 When electronic books are provided by the Internet web site 279, the billing and
21 collecting functions may be incorporated into the Internet web site 279. For example, a
22 subscriber may pay for an electronic book selection by entering a credit card number into
23 a data field of a page of the Internet web site 279. In this configuration, a separate billing
24 and collection system may not be required. Alternatively, the Internet web site 279 may
25 communicate information with the billing and collection system 278.

26 Electronic book delivery over the Internet may be handled using a number of
27 methods. In a method, the electronic book may be downloaded to the requesting home
28 system 258 immediately after the order has been processed. Alternatively, the electronic
29 book may be e-mailed to an e-mail address that is entered as part of the ordering process.

1 In another embodiment, as part of the ordering transaction process, the subscriber is
2 provided with location and authorization information that allows the subscriber to
3 retrieve the ordered electronic book at the subscriber's convenience. For delivery of
4 subscription electronic book products, like newspapers, magazines or other periodicals,
5 the Internet web site 279 can deliver the latest version of the product to the subscriber
6 automatically immediately upon logon by the subscriber to the Internet web site 279.
7 Electronic book data may also be embedded into continuous multicast streaming video,
8 audio, or data feeds.

9 d. Other Delivery Methods

10 A number of embodiments for the delivery of electronic books have been
11 addressed above. This subsection calls out these specific delivery embodiments, as well
12 as presents other delivery embodiments supported by this invention. Section I presented
13 a description of the operations center 250 and the uplink 254 used to transmit the
14 electronic book data over the video distribution system 208, using the use of an encoder
15 204. The embodiments presented below use a modular encoder 2541, which inserts the
16 electronic book text into the delivered signal and modular transmission subsystem 2542,
17 which transmits the actual signal. Together, the modular encoder 2541 and modular
18 transmission subsystem 2542 support the transmission functionality for each unique
19 delivery method embodiment. Section II presented a video connector 212 used to convert
20 the electronic book data embedded in the video signal to a format usable by the home
21 subsystem. The embodiments presented below use a modular connector 700 that receives
22 the delivered signal with embedded electronic book data, extracts the electronic book
23 data, and provides the electronic book data to the digital logic 609 for further processing.
24 The modular connector 700 supports the receive functionality for each unique delivery
25 method embodiment.

26 Figure 27 presents embodiments associated with the delivery of electronic books
27 over a coaxial or fiber cable system 2701 to a home system 1258. Electronic book data
28 is encoded for delivery by the modular encoder 2541, which is identical to the encoder
29 174 in Figure 1b and formatted and transmitted by the modular transmission subsystem

1 2542, which is identical to the uplink 254 in Figure 4. The signal is delivered over the
2 cable system 2701. This signal may provide for the dedicated or non-dedicated delivery
3 of electronic book data. This signal may also provide for ordering access from the home
4 system 1258 to the billing and collection system 278 or operations center 250, or the
5 signal may be a means to provide access to the Internet or other public network through
6 which electronic books are ordered and delivered. The cable system 2701 may be a
7 coaxial cable network, totally fiber network, hybrid fiber coax network, fiber to the curb
8 network, or any other cable distribution technology. The signal over the cable system
9 may be generated by a cable modem, in which an external cable modem 2702 is used to
10 receive the signal and provide the embedded electronic book data to the home system
11 1258 modular connector 700 for processing. Alternatively, the home system 1258 may
12 contain an internal cable modem 2705 which receives the signal and provides the
13 electronic book data to the modular connector 700 for processing. In each embodiment,
14 the modular connector 700 provides the embedded electronic book data to the digital
15 logic 609 for further processing.

16 In another embodiment, the signal delivered over the cable system is a video
17 signal. In one embodiment, the video signal is an analog video signal. In another
18 embodiment, the video signal is a digital video signal. The home system 1258 may
19 contain an internal cable receiver / tuner / demodulator 2706 to process the signal, and
20 provide the embedded electronic book data to the modular connector 700, which is
21 identical in the embodiment as video connector 212 in Figure 2. A set top terminal 2703,
22 or other device capable of receiving a cable video signal, such as a cable ready TV, or PC
23 with cable tuner (not shown), may process the video signal and deliver the video signal
24 to the connector 700 in the home system 1258 which extracts the embedded electronic
25 book data. Alternately, the set top terminal 2703, or other such device, may extract the
26 embedded electronic book data from the video signal and provide the electronic book
27 data to the modular connector 700 in the home system 1258.

28 In another embodiment, electronic book data may be embedded within the audio
29 signal, requiring an appropriate audio-capable modular connector 700 in the home system

1 1258 to extract the electronic book data from the audio signal for processing by the
2 digital logic 609. In one embodiment, the audio signal is an analog audio signal. In
3 another embodiment, the audio signal is a digital audio signal.

4 In yet another embodiment, the signal is a spread spectrum signal containing a
5 digital data stream, requiring an appropriate spread spectrum receiver and modular
6 connector 700 in the home system 1258 to extract the electronic book data for processing
7 by the digital logic 609. In this embodiment, the spread spectrum signal is transmitted
8 in the same bandwidth as the video or audio signal, but below the noise level.

9 Figure 28 presents embodiments associated with the delivery of electronic books
10 over a wireless broadcast system 2801 to a home system 1260. Electronic book data is
11 encoded for delivery by the modular encoder 2541 and formatted and transmitted by the
12 modular transmission subsystem 2542. The signal is delivered over the wireless
13 broadcast system 2801. This signal may provide for the dedicated or non-dedicated
14 delivery of electronic book data. This signal may also provide for ordering access from
15 the home system 1260 to the billing and collection system 278 or operations center 250,
16 or the signal may be a means to provide access to the Internet or other public network
17 through which electronic books are ordered and electronic book data is delivered. The
18 wireless broadcast system may be a microwave multipoint delivery system (MMDS),
19 local multipoint distribution system (LMDS), Instructional Television Fixed Service
20 (ITFS) system, or any other wireless data, video, or telephony broadcast system, including
21 point-to-point and point-to-multipoint microwave broadcast systems like those provided
22 by Teligent, Winstar digital wireless network, and ATT's wireless system. The signal
23 over the wireless broadcast system may be generated by a wireless modem, in which an
24 external wireless modem 2802 is used to receive the signal and provide the embedded
25 electronic book data to the home system 1260 modular connector 700 for processing.
26 Alternatively, the home system 1260 may contain an internal wireless modem 2805,
27 which receives the signal and provides the electronic book data to the home system 1260
28 modular connector 700 for processing. In each embodiment, the modular connector 700

1 provides the embedded electronic book data to the digital logic 609 for further
2 processing.

3 In another embodiment, the signal delivered over the wireless broadcast system
4 is a video signal. In one embodiment, the video signal is an analog video signal. In
5 another embodiment, the video signal is a digital video signal. The home subsystem
6 1260 may contain an internal wireless receiver / tuner / demodulator 2806 to process the
7 signal, and provide the embedded electronic book data to the modular connector 700. A
8 wireless set-top terminal 2803, or other device capable of receiving a wireless video
9 signal, such as a TV, or PC with a wireless receiver and tuner, may process the video
10 signal and deliver the video signal to the modular connector 700 in the home system
11 1260, which extracts the embedded electronic book data. Alternately, the set top terminal
12 2803, or other such device, may extract the embedded electronic book data from the
13 video signal and provide the data to the modular connector 700 in the home system 1260.

14 In another embodiment, electronic book data may be embedded within the audio
15 signal, requiring an appropriate audio-capable modular connector 700 in the home system
16 1260 to extract the electronic book data from the audio signal for processing by the
17 digital logic 609. In one embodiment, the audio signal is an analog audio signal. In
18 another embodiment, the audio signal is a digital audio signal.

19 In yet another embodiment, the signal is a spread spectrum signal containing a
20 digital data stream, requiring an appropriate spread spectrum receiver modular connector
21 700 in the home system 1260 to extract the electronic book data for processing by the
22 digital logic 609. In this embodiment, the spread spectrum signal is transmitted in the
23 same bandwidth as the video or audio signal, but below the noise level.

24 Figure 29 presents embodiments associated with the delivery of electronic books
25 over a satellite broadcast system 2901 to a home system 1280. Electronic book data is
26 encoded for delivery by the modular encoder 2541 and formatted and transmitted by the
27 modular transmission subsystem 2542. The signal is delivered over the satellite
28 broadcast system 2901. This signal may provide for the dedicated or non-dedicated
29 delivery of electronic book data. This signal may also provide for ordering access from

1 the home system 1280 to the billing and collection system 278 or operations center 250,
2 or the signal may be a means to provide access to the Internet or other public network
3 through which electronic books are ordered and electronic book data is delivered. The
4 satellite broadcast system 2901 can be a direct broadcast system like DirecTV and
5 EchoStar, a direct to home satellite broadcast system, video network distribution
6 broadcast system, a point-to-point or point-to-multipoint data VSAT system, a digital
7 audio broadcast system like WorldSpace, CD Radio, or XM, or a mobile data and
8 telephony satellite broadcast system like Iridium, Teledesic, or Globalstar. Alternatively,
9 the satellite broadcast system can consist of regionalized broadcast services or store and
10 forward communication services hosted on high flying balloons or on airplanes that
11 provide communication repeater services to an small geographic region. The signal over
12 the satellite broadcast system may be generated by a satellite data modem, in which an
13 external satellite data receiver 2902 is used to receive the signal and provide the
14 embedded electronic book data to the home system 1280 modular connector 700 for
15 processing. Alternatively, the home system 1280 may contain an internal satellite
16 receiver 2905 which receives the signal and provides the electronic book data to the home
17 system 1280 modular connector 700 for processing. In each embodiment, the modular
18 connector 700 provides the embedded electronic book data to the digital logic 609 for
19 further processing.

20 In another embodiment, the signal delivered over the satellite broadcast system
21 is a video signal. In one embodiment, the video signal is an analog video signal. In
22 another embodiment, the video signal is a digital video signal. The home system 1280
23 may contain an internal satellite video receiver 2906 to process the signal, and provide
24 the embedded electronic book data to the modular connector 700. A satellite receiver
25 2903, or other device capable of receiving a satellite video signal, such as a TV, or PC
26 with satellite receiver, may process the video signal and deliver the video signal to the
27 modular connector 700 in the home system 1280, which extracts the embedded electronic
28 book data. Alternately, the satellite receiver 2903, or other such device, may extract the

1 embedded electronic book data from the video signal and provide the data to the modular
2 connector in the home system 258.

3 In another embodiment, electronic book data may be embedded within the audio
4 signal, requiring an appropriate audio-capable modular connector 700 in the home system
5 1280 to extract the electronic book data from the audio signal for processing by the
6 digital logic 609. In one embodiment, the audio signal is an analog audio signal. In
7 another embodiment, the audio signal is a digital audio signal.

8 In yet another embodiment, the signal is a spread spectrum signal containing a
9 digital data stream, requiring an appropriate spread spectrum receiver modular connector
10 700 in the home system 1280 to extract the electronic book data for processing by the
11 digital logic 609. In this embodiment, the spread spectrum signal is transmitted in the
12 same bandwidth as the video or audio signal, but below the noise level.

13 Figure 30 presents embodiments associated with the delivery of electronic books
14 over a wired data network 3001 to a home system 1290. Electronic book data is encoded
15 for delivery by the modular encoder 2541 and formatted and transmitted by the modular
16 transmission subsystem 2542. The signal is delivered over the wired data network 3001.
17 This signal may provide for the dedicated or non-dedicated delivery of electronic book
18 data. This signal may also provide for ordering access from the home system 1290 to the
19 billing and collection system 278 or operations center 250, or the signal may be a means
20 to provide access to the Internet or other public network through which electronic books
21 are ordered and electronic book data is delivered. The wired data network 3001 can be
22 metallic wire or fiber, supporting any of a number of communication standards including
23 HDSL, ADSL, DSL, ISDN, T1, T3, SONET, ATM, X.25, frame relay, Switched
24 MultiMegabit Data Service (SMDS), or others. The signal sent over the wired data
25 network may be generated by a data modem or transmission device, in which the
26 appropriate modem, interface device, or Data Terminating Equipment (DTE) device is
27 used to receive the signal and provide the embedded electronic book data to the home
28 system 1290 modular connector 700 for processing. Embodiments of such receiving
29 devices are shown in Figure 30 as HDSL modem 3002, ADSL modem 3003, DSL

1 modem 3003, ISDN Terminal equipment (TE) device 3005, T1 Digital service unit
2 (DSU) 3006, T3 DSU 3007, Fiber user network interface device (UNI) 3008, ATM UNI
3 3009, X.25 DTE 3010, Frame relay assembler / disassembler (FRAD) 3011, and SMDS
4 subscriber network interface device (SNI) 3012. Alternatively, the home system 1290
5 may contain an internal modem or DTE 3013, which receives one or more signal types
6 and provides the received signal with embedded electronic book data to the home system
7 1290 modular connector 700 for processing. Finally, the home system 1290 may be
8 attached to a wired LAN using a transceiver. In this embodiment, electronic book data
9 may be delivered over the LAN at any time. One example of how this embodiment may
10 be used is in a university environment where each student has an electronic book home
11 subsystem attached to the LAN. Professors can then deliver textbooks and assignments
12 to selective students. In each embodiment, the modular connector 700 provides the
13 embedded electronic book data to the digital logic 609 for further processing.

14 Figure 31 presents embodiments associated with the delivery of electronic books
15 using the public switched telephone network (PSTN) 3101 to a home system 1310.
16 Electronic book data is encoded for delivery by the modular encoder 2541 and formatted
17 and transmitted by the modular transmission subsystem 2542. The signal is delivered
18 over the PSTN 3101. This signal may provide for ordering access from the home system
19 1310 to the billing and collection system 278 or operations center 250, or the signal may
20 be a means to provide access to the Internet or other public network through which
21 electronic books are ordered and electronic book data is delivered. The signal sent over
22 the PSTN may be generated by a data modem or transmission device, in which the
23 appropriate modem 3102 is used to receive the signal and provide the embedded
24 electronic book data to the home system 1310 modular connector 700 for processing.
25 Alternatively, the home system 1310 may contain an internal modem 3103, which
26 receives the signal and provides the received signal with embedded electronic book data
27 to the home system 1310 modular connector 700 for processing. In each embodiment,
28 the modular connector 700 provides the embedded electronic book data to the digital
29 logic 609 for further processing.

1 Figure 32 presents embodiments associated with the delivery of electronic books
2 using wireless personal communications system (PCS) 3201 to a home system 1310.
3 Electronic book data is encoded for delivery by the modular encoder 2541 and formatted
4 and transmitted by the modular transmission subsystem 2542. The signal is then
5 delivered over the PCS network 3201. The wireless PCS system may be, for example,
6 a wireless LAN, digital cellular telephony network, analog cellular telephony network,
7 digital cellular radio system, analog cellular radio system, digital pager network, analog
8 pager network, or Personal Communication Network (PCN). This signal may provide
9 for the dedicated or non-dedicated delivery of electronic book data. This signal may also
10 provide for ordering access from the home system 1320 to the billing and collection
11 system 278 or operations center 250, or the signal may be a means to provide access to
12 the Internet or other public network through which electronic books are ordered and
13 electronic book data is delivered. A wireless PCS receiver 3202 is used to receive the
14 signal and provide the embedded electronic book data to the home system 1320 modular
15 connector 700 for processing. Alternatively, the home system 258 may contain an
16 internal wireless PCS receiver 3203 which receives the signal and provides the received
17 signal with embedded electronic book data to the home system 1320 modular connector
18 700 for processing. In each embodiment, the modular connector 700 provides the
19 embedded electronic book data to the digital logic 609 for further processing.

20 Returning to Figure 19, several embodiments are shown associated with the
21 delivery of electronic books using a national or local television broadcaster's signal. The
22 signal from the national broadcaster 1110 can be delivered to the home subsystem 258',
23 285'', or 258''' using a satellite system 1122, using a broadcast affiliate 1112 terrestrially,
24 or using a local cable system 1114. Alternatively, the local television broadcast affiliate
25 1112 can originate the signal which can be delivered to the home system 258', 258'' or
26 258''' terrestrially, or using a local cable system 1114. In one embodiment, the video
27 signal is an analog video signal and the electronic book data is embedded in the video
28 signal. In another embodiment, the video signal is a digital video signal and the
29 electronic book data is carried as an independent data stream. In another embodiment,

1 electronic book data may be embedded within the audio signal. In one embodiment, the
2 audio signal is an analog audio signal. In another embodiment, the audio signal is a
3 digital audio signal.

4 In yet another embodiment, the signal is a spread spectrum signal containing a
5 digital data stream, requiring an appropriate spread spectrum receiver modular connector,
6 such as the connector 700 of Figure 32, in the home system 258', 258" or 258''' to extract
7 the electronic book data for processing by the digital logic 609. In this embodiment, the
8 spread spectrum signal is transmitted in the same bandwidth as the video or audio signal,
9 but below the noise level.

10 Alternatively, several embodiments are associated with the delivery of electronic
11 books using a national or local radio broadcaster's signal. The signal from the national
12 radio broadcaster can be delivered to the home system 258', 258" or 258''' using the
13 satellite system 1122, or using a broadcast affiliate 1122. Alternatively, the radio
14 broadcast affiliate 1122 can originate the signal, which can be delivered to the home
15 system 258', 258" or 258''', terrestrially. In one embodiment, the audio signal is an
16 analog audio signal and the electronic book data is embedded in the audio signal. In
17 another embodiment, the audio signal is a digital audio signal and the electronic book
18 data is carried as an independent data stream. In yet another embodiment, the electronic
19 book data is embedded in a sub-carrier of the analog audio broadcast. In a final
20 embodiment, the signal is a spread spectrum signal containing a digital data stream,
21 requiring an appropriate spread spectrum receiver modular connector 700 in the home
22 system 258', 258", or 258''' to extract the electronic book data for processing by the
23 digital logic 609. In this embodiment, the spread spectrum signal is transmitted in the
24 same bandwidth as the audio signal, but below the noise level.

25 In any of the delivery methods above, the delivery path may be used to establish
26 connectivity to the Internet, allowing Internet delivery of electronic book data as
27 presented early in this section.

28 In an alternative delivery embodiment, the electronic book system can be
29 modified, as was presented in Figure 15 and discussed above, to be used at public

1 libraries, schools, bookstores, newspaper stands or stand-alone kiosks, for example.
2 Public newsstands for electronic books and periodicals may be conveniently located, such
3 at the corner store on a New York City street corner, at an airport, or even on an airplane.
4 The main unit at the public library, school, bookstore, newsstand, or kiosk may be the file
5 server 900 as shown in Figure 15. The file server 900 is a large electronic memory unit
6 that can store thousands of books, newspapers, or periodicals. Various electronic storage
7 means may be used in the file servers, such as hard disks, read-write CD ROMs and read-
8 only CD ROMs. The controller 908 in Figure 15 is able to download books to public
9 viewers 912. The bookstores or libraries can rent the public viewer 912 to customers
10 with the text for one or two books loaded onto the public viewer 912. Alternatively, the
11 customer may own the viewer. The customer returns to the file server 900 from time to
12 time to receive textual data for a book, which the customer can read and delete or store
13 permanently on the customer's own home system 258. Based on the specific information
14 known about a customer, advertisements contained in the electronic books may be
15 customized, creating a unique version of the downloaded newspaper, magazine, or book
16 for each customer.

17 Electronic book data also may be delivered as content stored on physical devices
18 like a floppy disk, magnetic tape, Smart Card device, Memory Stick device, or any other
19 portable memory storage device and provided to a subscriber for transfer to the home
20 system 258. Each electronic book memory storage device can contain a unique identifier,
21 one or more electronic book files, and associated viewing authorization information.
22 Viewing of any electronic book file from the memory device may be supported without
23 restriction. Alternatively, some or all electronic book files on the memory device may
24 be available for limited viewing or may require authorization from the billing and
25 collection system 278 prior to being viewed. In this case, the home system 258 may
26 contact the billing and collection system 278 for authorization prior to viewing.

27 When the electronic book is delivered on a portable storage medium, such as the
28 Smart Card device or the Memory Stick device, the electronic book and its storage
29 medium may be packaged in a manner that protects the storage device, and also provides

1 a simulation of an actual book. Figure 33 is an example of a storage device 2600 that
2 stores an electronic book portable storage medium. A Smart Card 2601 is held in place
3 in a recess 2602 in a back panel 2603 of the storage device 2600. A front panel 2604 is
4 attached to the back panel 2603 by a hinge 2605 that is placed at a back spine 2606 of the
5 storage device 2600. The front panel 2604 may be operated to close over the back panel
6 2603 to completely cover the storage medium 2601. The front panel 2604 may
7 incorporate a clasp, or similar locking device, that engages a corresponding detent 2608
8 in the back panel 2603 so as to securely close the storage device 2600.

9 The front panel 2604 of the storage device 2600 may include a cover 2609 that
10 replicates a front cover, or dust jacket of a hard copy book corresponding to the electronic
11 book. Similarly, the back panel 2603 may include a display similar to that existing on a
12 back cover, or dust jacket of the corresponding hard copy book. A cover such as the
13 cover 2609 may be a piece of paper or similar material that is inserted into the front panel
14 2604, for example. Alternately, the cover 2609 may be a permanently fixed replication
15 of the front cover of the corresponding hard copy book. The resulting storage device
16 2600 may thus emulate the corresponding hard copy book, and may be stored on an actual
17 bookshelf, or other storage area, in the same manner as the corresponding hard copy
18 book.

19 Electronic book data may also be delivered from a machine or other device to the
20 home system 258. Figure 34 shows a system 2700 of machines 2701 that are coupled by
21 a communications network 2702. The communications network 2702 may be any wired
22 or wireless system previously described herein. The communications network 2702 may
23 also be an electrical distribution system, such as a home wiring system that is rated at 110
24 and 220 volts, for example. The system 2700 may include an interface 2703 through
25 which the viewer 266 communicates with the machines 2701. For example, the interface
26 2703 may be a plug-in device that may be inserted into a 110-volt wall socket. Such a
27 device 2703 may include a wired or wireless interface to the viewer 266.

28 The machines 2701 may include a microprocessor 2710, a memory 2711, and a
29 transceiver 2712, which may be incorporated in VLSI, for example. Included in the

1 memory 2711 may be one or more electronic books that may be downloaded to the
2 viewer 266, or otherwise viewed by the viewer 266 using the interface 2703. For
3 example, a home appliance could include in its memory, an electronic technical manual
4 related to the home appliance. To access the electronic technical manual, the viewer 266,
5 through the interface 2703, may transmit a code or similar "handshake" to cause the
6 microprocessor 2710 to transmit the electronic technical manual, using the transceiver
7 2712, to the viewer 266.

8 The electronic book system 200 may also incorporate a book preview mechanism.
9 Such a preview mechanism may provide the look and feel of browsing through a
10 selection of books or magazines in a bookstore. Thus, the subscriber may browse
11 electronic books, electronic magazines, and electronic newspapers, for example, before
12 purchasing the electronic books, newspapers or magazines. Electronic book previews
13 were previously described with respect to Figures 14i and 14j. Such electronic book
14 previews may be provided as an on-line service, an off-line service, or both.

15 The on-line electronic book preview mechanism may use an Internet web site,
16 such as the web site 279, to display electronic book previews. To obtain an electronic
17 book preview, the subscriber may communicate with, or access, the web site 279 using
18 the viewer 266, or one of the other devices shown in Figures 21a - 21g including the set
19 top terminal 1220, the personal computer 1172 and the television 1171, for example.
20 Once in communication with the Internet web site 279, the subscriber may select an
21 electronic book preview to view from a list or menu, such as the menu 866 shown in
22 Figure 13, for example, of available electronic book previews. The selected electronic
23 book preview may then be displayed on a web page of the Internet web site 279, and may
24 be viewed on the viewer, 266, the television 1171 or the personal computer 1172, for
25 example.

26 Other on-line sites may be used to display electronic book previews. In general,
27 any addressable node, such as an e-mail address, for example, in a telecommunications
28 network may be used as a display site for electronic book previews.

1 The electronic book previews may also be provided off-line, to be downloaded
2 to the home system 258, for example. The subscriber may access the Internet web site
3 279 and download an electronic file that includes the electronic book preview. The
4 electronic book preview may be stored in the library or the viewer, for example. The
5 subscriber may then view the electronic book preview using the viewer 266, the
6 television 1171, or the personal computer 1172, for example.

7 When the electronic book previews are provided for downloading to the home
8 system 258, the electronic book previews may be provided in encrypted format or in
9 unencrypted format.

10 The delivery methods discussed above that allow for dedicated, full time delivery
11 can be used to provide continuous distribution of electronic book data including
12 requested electronic books from subscribers, electronic books to be broadcast to all
13 subscribers, updated menu contents, and updated advertising. For the delivery methods
14 discussed above that allow for non-dedicated or user established connectivity, the
15 operations center 250 may manage the timing and delivery of content by delivering the
16 electronic book only when requested, or periodically, to ensure delivery for those home
17 systems that may not be able to receive the delivery. Finally, the delivery methods
18 discussed above that are capable of two-way communication may be used to provide a
19 return path to the operations center 250 or billing and collection system 278 for the
20 purpose of ordering or requesting updated electronic book information.

21 Additionally, although the home system 258 is presented as an independent device
22 that directly interfaces with the delivery system 200, the home system 258 may connect
23 to the delivery system 200 through a set top terminal, TV, PC, radio, or any other device
24 capable of receiving the signal provided by the delivery system 200. Additionally, the
25 home system 258 may not be an independent apparatus, having some or all of its
26 functionality supported within the set top terminal, TV, PC, radio, or any other device
27 capable of receiving the signal provided by the delivery system.

1 e. Alternative Ordering Methods

2 Any of the delivery methods described in the section above are viable
3 embodiments for providing access from the home system 258 to the billing and collection
4 system 278 or operations center 250. In an embodiment, the modular connector 701, as
5 shown in Figures 6b and 8, may be used to provide the specific protocol formatting and
6 transmission processing to allow the home system 258 to use the communication path.
7 In the embodiment where the PSTN is used to provide access, the modular connector 701
8 includes the phone connector 270 and the modem 611 as depicted in Figure 6b. In the
9 embodiment where the cellular phone system is used to provide access, the modular
10 connector 701 includes the cellular phone or PCN phone 611' as depicted in Figure 6b.

11 f. Mobile Environments

12 A feature provided by the delivery methods using a wireless broadcast system
13 2801, satellite broadcast system 2901, wireless personal communication system 3201, or
14 terrestrial television broadcast system, is mobility of the electronic book home system or
15 viewer 266. This mobility allows for ordering and receiving electronic book data anytime
16 or anywhere, from sitting on a beach in Florida to sitting on a bus in New York City.
17 This mobility allows for the delivery of electronic book data subscription products such
18 as daily newspapers, monthly magazines, or books from book-of-the-month clubs. These
19 subscription products may be delivered automatically to the appropriate home system 258
20 or electronic book viewer 266. Enhanced end-to-end error correction techniques can be
21 added to the transmission system to ensure higher probability of receipt for these mobile
22 environments. Additionally, transmission methods may be implemented that resend
23 packets of electronic book data, changing their delivered order on each resend, to improve
24 likelihood of receipt. For lower bandwidth mobile environments, an electronic book file
25 may be broken up into packets and the packets sent a limited number of times. If the
26 electronic book file is not received completely, the electronic book viewer 266 may
27 initiate a request to the operations center 250 to resend only that portion of the electronic
28 book file yet to be received.

VIII. Electronic Commerce Features

Electronic commerce features permit users of electronic books to shop for products and services using an electronic book viewer. Users can view information about products and services, electronically purchase them, and electronically download digital products. The electronic commerce features also permit tracking of purchases by particular users and purchases of particular products for recommending, for example, other products and services to users. For certain products, such as music and video, a user may download a sample of the product before deciding whether to purchase it.

The processing for providing electronic commerce features is illustrated in flow charts described below. This processing may be implemented in software or firmware, including software modules, for execution by the viewer 266, the library 262, or a combination of them. Information on products or services may be locally stored for access by the viewer 266 or the library 262, or accessed and downloaded via a network such as the Internet using the delivery mechanisms described above.

Figure 35 is a flow chart of a method 3500 for providing functions for electronic commerce in conjunction with display of an electronic book. A user selects an electronic book for viewing using, for example, a displayed menu (step 3502). The viewer 266 displays the electronic book (step 3504) and displays pages of the electronic book as selected by the user (step 3506). When viewing the electronic book, the user may enter functions relating to electronic commerce features using a cursor-control device or other input device (step 3508) and, in response, the viewer 266 executes the requested function (step 3510). The viewer 266 continues to display pages of the electronic book and execute selected electronic commerce functions until the user closes the electronic book, as determined by step 3512. If the user selects another electronic book for viewing, as determined by step 3514, the viewer 266 displays that electronic book (step 3504).

Figure 36 is a schematic illustrating a viewer 266 with a screen 3520 having sections providing for electronic commerce. Screen 3520 includes a displayed page 3522 of an electronic book, which may include text, as shown, or other types of information such as graphics, pictures, or any type of multimedia information. Page 3522 also

1 includes a task bar 3528 providing sections for various electronic commerce features,
2 further explained below. The terms section refers to a definable portion of the screen,
3 and the phrase task bar refers to a collection of sections for permitting selection of
4 various commands. A user may select the various sections by using a cursor-control
5 device to select or "click on" the section or by entering a particular command using a
6 keyboard or other input device. The act of selecting a section may involve, for example,
7 positioning the cursor or a pointer over the section using the trackball 743 and depressing
8 the selection button 745 to "click on" the section. Other cursor-control devices, including
9 peripheral devices, may be used to select a section.

10 A menu section 3530 permits a user to access a menu or index of stored electronic
11 books in order to choose one for viewing, and examples of such menus are provided in
12 Figures 14a-14j. An information section 3532 permits a user to view information
13 concerning a particular product or service. A purchase section 3534 permits a user to
14 submit a request to purchase a particular product or service. A sample section 3536
15 permits a user to view a sample relating to a particular product. A catalog section 3538
16 permits a user to access an electronic catalog of products and services. A browser section
17 3560 permits a user to access a web browser for retrieving content from the World Wide
18 Web. Page turn sections 3562 and 3564 permit a user to page backward and forward,
19 respectively, in the displayed electronic book. Task bar 3528 can alternatively include
20 various other sections for retrieving and manipulating displayed electronic books.

21 Page 3522 also illustrates how an electronic book may include an identification
22 section 3524 for identifying a particular product or service. The identification may
23 include a text string, icon, or other type of symbol. As shown in section 3526, it may also
24 include a hypertext link. The identification of a product or service in identification
25 section 3524 may itself be a hypertext link. The identified product or service may relate
26 to information in the displayed electronic book. For example, when the user views a
27 particular electronic book, the viewer 266 may display an identification of other
28 electronic books by the same author. If the user views an electronic book on sports, the
29 viewer 266 may display an identification of sports equipment for purchase. If the user

1 views an electronic book concerning travel to a particular city, the viewer 266 may
2 display an identification of entertainment events for which the user may purchase tickets.
3 These are only a few examples of displaying products or services for electronic
4 commerce, and many other possibilities exist.

5 Figure 37 is a flow chart of a method 3570 for displaying product or service
6 information concerning products or services selected by a user. A user first selects a
7 product or service identified in identification section 3524 and then selects information
8 section 3532. The viewer 266 receives the identified product or service (step 3572). The
9 viewer 266 retrieves and displays information concerning the selected product or service
10 (step 3574). The product or service information may be stored in a database, such as in
11 library menu 600, and accessed locally or accessed via a network, such as the Internet,
12 and downloaded using one or more of the delivery mechanisms described above. In
13 addition, the viewer 266 may select and display an identification of related products (step
14 3576) for potential selection by the user. The viewer 266 may also optionally select and
15 display an advertisement (step 3578), the selection of which may be based upon the
16 product or service selected by the user or other information related to the user. The
17 advertisements may be targeted to particular users as described in the co-pending
18 application entitled "TARGETED ADVERTISEMENT USING TELEVISION
19 DELIVERY SYSTEMS" and identified above. Upon viewing information about a
20 product or service, the user may select the purchase section 3534 in order to purchase a
21 particular product or service. The viewer 266 determines if the user selects the purchase
22 section 3534 (step 3580) and, if so, it executes a purchase routine (step 3582), explained
23 below. The viewer 266 also records statistics (step 3584), as explained below, in order
24 to record information concerning purchases and requests for information concerning
25 particular products and services.

26 Figure 38 is a schematic illustrating a screen 3590 for display of product or
27 service information in method 3570. Upon selection of a product or service in
28 conjunction with information section 3532, the viewer 266 displays an information
29 section 3592 having information concerning the identified product or service. The

1 information may include, for example, a textual description of the product or service,
2 features of the product or service, a photograph or graphical representation of the product
3 or service, or any type of multimedia information concerning the product or service. An
4 information section 3594 may display information concerning related products or services
5 that may be of interest to the user. The viewer 266 also optionally displays an
6 advertisement in an advertisement section 3596, the advertisement potentially being
7 selected based upon information related to the user and thus targeted to the user. The
8 sections 3592 and 3596 optionally may be expanded to cover the entire screen of the
9 viewer 266 upon selection of an expand feature by the user. The user may subsequently
10 shrink the expanded section to its original size. In addition, the sections 3592, 3594 and
11 3596 may incorporate a feature that allows the user to turn the sections off so that none
12 or some of the sections are not displayed. This feature may be available on a page-by-
13 page basis or for an entire electronic book. The feature may be available in advance of
14 viewing, or only after the sections have been displayed for a specified time.

15 Figures 39a and 39b are a flow chart of a method 3600 for permitting a user to
16 purchase a product or service. Method 3600 is typically invoked upon a user's selection
17 of the purchase section 3534. The viewer 266 receives an identification of a product or
18 service (step 3602), which may occur through a user's selection of a product or service
19 identified in section 3524 or in an electronic catalog as described below. The viewer 266
20 determines whether to automatically generate an order form for the purchase request (step
21 3604). The viewer 266 typically has stored information concerning the user, such as the
22 user's name, address, and credit card number. Also, the viewer 266 receives
23 identification of a product or service in step 3602.

24 Therefore, the viewer 266 can automatically compile the user information and
25 identified product or service information into an electronic order form for submission by
26 the user. If auto order form generation is invoked, the viewer 266 automatically generates
27 the electronic order form (step 3610) and receives the user's submission of the electronic
28 order form (step 3612). The user typically may alter or change the information in the auto
29 generated form prior to submitting it. Otherwise, if auto form generation is not invoked,

1 the viewer 266 presents an electronic order form for completion by the user (step 3606)
2 and receives the user's submission of it (step 3608). An example of an electronic order
3 form is described below. The determination of whether to use auto order form generation
4 may be set by a manufacturer or distributor of the viewer; alternatively, a user may set
5 that option using a set-up menu or other mechanism for setting operating parameters of
6 the viewer 266.

7 Upon submission of the electronic order form, the viewer 266 may optionally
8 encrypt the order form and generate a digital signature for it upon transmission of the
9 form to a server for order processing (step 3614). If the digital signature is not valid, as
10 determined by step 3614, the viewer 266 may return an error message to the user (step
11 3618). Various types of encryption are known in the art. Use of digital signatures is
12 described in copending U.S. Application Serial Number 09/400,296, entitled
13 ELECTRONIC BOOK SECURITY AND COPYRIGHT PROTECTION SYSTEM, the
14 disclosure of which is hereby incorporated by reference. Digital signatures may include
15 a computed digest of an encrypted message, and the digest is sent with the encrypted
16 message. A recipient decrypts the digital signature and recomputes the digest from the
17 received information. If the digests match, the message was received intact from the
18 sender and is authenticated.

19 The viewer 266 may also receive submission of a digital coupon, if one is
20 available (step 3620). A digital coupon may be displayed in a section on the viewer 266
21 and permit a user, upon selection for submission of it, to receive a discounted price for
22 a selected product or service. Digital coupons may be time-limited such that they are
23 displayed using time-based information and are thus only valid for a particular time
24 period. Other parameters or criteria may also be used for determining when to display
25 digital coupons and the content of them.

26 In certain situations the viewer 266 may permit a user to negotiate a price for a
27 product or service. In this case, the viewer 266 determines if the price received in the
28 electronic order form is an offered price (step 3622). If it is an offered price, the viewer
29 266 or server determines whether to accept the offered price based on particular criteria

1 (step 3624). For example, the viewer 266 or server may determine if the offered price is
2 within a range of acceptable prices and if the user is entitled to a particular price based
3 upon repeat purchases. The viewer 266 or server may also determine if rebates or
4 discounts are currently available for the identified product or service for which purchase
5 is requested. If the price is accepted, as determined in step 3626, the viewer 266 displays
6 an indication of the acceptance (step 3630); otherwise, if the price is not accepted, the
7 viewer 266 displays an indication of the non-acceptance and permits the user to enter
8 another offered price (step 3628).

9 The viewer 266, potentially in conjunction with a server, executes the purchase
10 requested in the electronic order form (step 3632). Payment is attempted using the
11 entered credit card or other payment-related information (step 3634). If payment is not
12 approved, the viewer 266 may display an error message (step 3636). Upon approval of
13 payment, the viewer 266 arranges for delivery of the product or service (step 3638). For
14 a digital product, the user can receive the product electronically. A digital product is any
15 product capable of being electronically stored in digital form; examples include electronic
16 books, software applications, music, video, photographs, animations, multimedia
17 information, and slide shows. The viewer 266 determines if the user purchased a digital
18 product (step 3640) and, if so, whether the user requested electronic download of the
19 product (step 3644). If requested, the product is electronically downloaded to the viewer
20 266 or library 262 (step 3646). Otherwise, other delivery is arranged and the viewer 266
21 provides an indication of the alternative delivery (step 3642). For example, the product
22 may be mailed to the user. The viewer 266 also records statistics (step 3648), as
23 explained below.

24 Figure 40 is a schematic illustrating a screen 3650 having an electronic order form
25 for permitting a user to submit a request to purchase a product or service as executed by
26 method 3600. Page 3522 presents an electronic order form 3652 upon a user's selection
27 of purchase section 3534. Electronic order form 3652 may be presented as an inset image
28 within a displayed electronic book in page 3522, as an overlaid image in the displayed
29 electronic book, or in place of the displayed electronic book.

As shown, the electronic order form 3652 includes sections for the user to enter information for use in submitting a purchase request. In particular the electronic order form 3652 includes a user information section 3654 for a user to entered identifying information such as their name and address. A product/service identification section 3656 permits a user to enter an identification of a product or service to purchase. A payment information section 3658 permits a user to enter a credit number or other payment-related information. An offered price section 3659 permits a user to enter an offered price, if the user desires to negotiate a price for the product or service. A digital download section 3661 permits a user to request digital downloading for purchased digital products. A submit section 3660, upon selection by the user, permits the user to submit electronic order form 3652 and its contents for a purchase request. Screen 3650 also illustrates display of an optional digital coupon in a digital coupon section 3662 for use with purchase of a corresponding product or service. The digital coupon may also be displayed in screen 3520 when the user views a particular electronic book.

Figure 41 is a flow chart of a method 3670 for recording statistics concerning requests to purchase or view information concerning products and services. The viewer 266 may record these statistics for use in recommending related products or services to a user or for selecting particular advertisements for display to the user. In method 3670, the viewer 266 or a corresponding server records an identification of a purchased product or service in a product/service data structure (step 3672) and also records an identification of the purchased product or service in a user data structure (step 3674). The viewer 266 optionally records other information in the product and user data structures such as a time and date of the purchase, amount of the purchase, quantity of the purchase, version of a purchased product, and whether the user entered a purchase request or product/service information request.

The product/service data structure can include a table or series of tables for each product or service, storing information concerning purchases or requests to view information concerning the product or service. The user data structure can include a table or series of tables for each user, storing information concerning purchases and requests

to view product or service information by the user. The following provides an example of tables for storing statistics.

1	product/service 1
	number of purchases
	number of information requests
P(1)	product/service 1; purchase 1
	amount of purchase
	date and time of purchase
	quantity of purchase
	version of purchase
	...
P(N)	product/service 1; purchase N
	amount of purchase
	date and time of purchase
	quantity of purchase
	version of purchase
I(1)	product/service 1; information request 1
	time and date of request
	...
I(N)	product/service N; information request N
	time and date of request

1	user 1
	purchase request 1
	...

	purchase request N
	information request 1
	...
	information request N
	...
1	N
	user N
	purchase request 1
	...
	purchase request N
	information request 1
	...
	information request N

2 Therefore, tables may exist for each product or service and for each user to record and
 3 store the statistics. A purchase request for particular product by a particular user, for
 4 example, may be linked to the table storing information for that purchase request, thus
 5 providing a mechanism to cross-reference the statistics. Use of such linkages using
 6 foreign keys is known in the art with respect to relational database structures. Other data
 7 structures, such as an object-oriented database, may also be used.

8 Figure 42 is a flow chart of a method 3680 for providing a user with a sample
 9 concerning a product or service. In method 3680, the viewer 266 receives an
 10 identification of a product (step 3682) and selection of sample section 3536 (step 3684).
 11 The viewer 266 or corresponding server determines if a sample is available for the
 12 identified product, which may be accomplished by accessing an index of samples cross-
 13 referenced with the corresponding products and services (step 3686). If no sample is
 14 available, the viewer 266 can display an error message (step 3688). If a sample is
 15 available, the viewer 266 retrieves the sample and delivers it to the user (step 3690). The
 16 samples may be stored in a database, such as in library memory 600, and accessed locally

1 or accessed via a network, such as the Internet, and downloaded using one of the deliver
2 mechanisms described above. The samples may include, for example, the following: a
3 video clip (step 3692); an audio clip (step 3694); a portion of an electronic book such as
4 the first chapter (step 3696); an image (step 3698); a slide show or portion of it (step
5 3700); an animation (step 3702); or other type of sample (step 3704).

6 Figure 43 is a schematic illustrating a screen 3720 for displaying a sample
7 concerning a product or service. Upon a user's selection of sample section 3536, the
8 viewer 266 displays a product sample section 3722 and presents the requested sample in
9 it. For an audio sample, the viewer 266 uses speakers to provide the audio clip and need
10 not necessarily display product sample section 3722. The audio clip or other audio
11 information may be provided using speaker/microphone 608'.

12 Figure 44 is a flow chart of a method 3730 for providing a user with an electronic
13 catalog identifying products or services. The electronic catalog permits the user to shop
14 on-line for products or services. The electronic catalog may include a static version in
15 which a user can view information about products and services, and an interactive version
16 in which the user can order products or services on-line. In method 3730, the viewer 266
17 receives a request for an electronic catalog through a user's selection of catalog section
18 3538 (step 3732). The viewer 266 or corresponding server determines whether to provide
19 a custom catalog (step 3734). If the viewer 266 or server does not provide a custom
20 catalog, the viewer 266 may alternatively generate and display a default catalog (step
21 3736).

22 For the custom catalog, the viewer 266 may access the user data structure storing
23 products or services for which the user has entered purchase or information requests (step
24 3738). The viewer 266 determines if the user data structure contains any identification
25 of products or services previously purchased or for which information was requested
26 (step 3740). If the user data structure contains no such identification, the viewer 266
27 generates and displays the default catalog (step 3736). A default catalog may be
28 generated from a sample of products or services based, for example, upon empirical
29 evidence to determine the most popular products and services. A manufacturer or

1 distributor of the viewer may prestore that default catalog or make it available for
2 downloading into the viewer via a network.

3 Otherwise, the viewer 266 retrieves the identification of the products and services
4 (step 3742) and also retrieves identification of related products and services (step 3744).
5 The viewer 266 may include tables or other data structures of related products or services
6 linked to particular products or services. The viewer 266 retrieves information for the
7 identified products or services (step 3746), and compiles the identification of the products
8 or services and the information into an electronic catalog (step 3748), which is then
9 displayed to the user (step 3750). Alternatively, the viewer 266 may generate a custom
10 electronic catalog by querying the user to determine the user's preferences, for example,
11 and retrieve products and services based upon those preferences. The electronic catalog
12 may be displayed as an inset image within a displayed electronic book, as an overlaid
13 image on the displayed electronic book, or in place of the displayed electronic book.

14 If the user requests product information through selection of information section
15 3532 (step 3752), the viewer 266 executes product information routine 3570 (step 3754).
16 If the user requests a purchase of a product or service through selection of purchase
17 section 3534 (step 3756), the viewer 266 executes purchase routine 3600 (step 3758).
18 The viewer 266 continues to display the electronic catalog and execute purchase or
19 information requests until the user closes the electronic catalog, as determined by step
20 3760.

21 Figure 45 is a schematic illustrating display of an electronic catalog in a screen
22 3770. Upon generation of an electronic catalog, either custom or default, the viewer 266
23 in page 3522 displays an interactive electronic catalog in an electronic catalog section
24 3772, including identification of products or services in sections 3774, 3776, and 3778.
25 Only identification of three products or services is shown for illustrative purposes;
26 electronic catalog section 3772 may display more or fewer. The electronic catalog, as
27 shown, may be displayed within an electronic book, as an inset or overlaid image, or
28 displayed in place of an electronic book in page 3522.

1 Figure 46 is a flow chart of a method 3780 for permitting a user to access and use
2 a web browser in the viewer 266. In method 3780, the viewer 266 receives a user's
3 selection of browser section 3560 (step 3782). In response, the viewer 266 launches a
4 web browser program (step 3784). Using the web browser, the viewer 266 displays web
5 pages as selected by the user (step 3786) until the user closes the browser (step 3788).
6 Web browsers are known in the art and include, for example, the Netscape Navigator
7 program by Netscape Communications, Inc. and the Internet Explorer program by
8 Microsoft, Inc. Figure 47 is a schematic illustrating a web browser screen 3800 for
9 displaying a web browser 3802 within a viewer 266. The web browser screen 3800 may
10 be displayed as an inset image within a displayed electronic book, as an overlaid image
11 on the displayed electronic book, or in place of the displayed electronic book.

12 Figure 48 is a flow chart of a method 3810 for retrieving and displaying web
13 pages as selected by a user. The user may retrieve web pages either by using the browser
14 program through selection of browser section 3560 or by directly selecting hypertext link
15 3526. In method 3810, the user selects hypertext link 3526 (step 3812). In response, the
16 viewer 266 launches web browser 3802 (step 3814) and, using web browser 3802,
17 retrieves a web page identified by the hypertext link (step 3816). The viewer 266
18 continues to display web pages as selected by the user (step 3818) until the user closes
19 web browser 3802 (step 3820).

20 Upon completion of processing for various electronic commerce features, as
21 described above, viewer 266 may return by default to display screen 3520. Alternatively,
22 various other screens may be used for displaying other information potentially of interest
23 to the user. The screens may display product and service information, and potentially
24 other information, using a wide variety of types of content, including multimedia
25 information, for enhancing a user's experience in interacting with the viewer and the ease
26 with which the user may use the various electronic commerce features.

27 A variety of electronic commerce features have been described for obtaining
28 information concerning products or services and purchase of them. Also, a variety of
29 delivery mechanisms, systems and methods have been described for ordering and delivery

- 1
- 2
- 3
- 4